

# 2008 TRACK & RACE CAR PRE- 1993 TOURING CAR CHAMPIONSHIP

## 1. SPORTING REGULATIONS - GENERAL

### 1.1 Title & Jurisdiction:

The 2008 TRACK & RACE CAR PRE 1993 TOURING CAR CHAMPIONSHIP is organised and administered by the BARC in accordance with the General Series Prescriptions of the Royal Automobile Club Motor Sports Association (MSA) and these Championship Regulations. The organisers reserve the right to issue additional statements clarifying items in the rules and regulations and all such statements will be issued to all registered drivers by posting to the address details on the registration form.

MSA Championship Permit No: **CHR2008 / 041** MSA Championship Grade: **D**  
Race Status: **National B**

### 1.2 Officials:

1.2.1	Championship Co-ordinator:	Nicola Bush	BARC
1.2.2	Drivers Reps:	David Howard Tim Scott Andrews	CTCRC CTCRC
1.2.3	Licensed Eligibility Scrutineers:	Dennis Bown Matthew Godber (Deputy)	BARC BARC
1.2.3	Championship Stewards:	Dale Wells Rick Smith Bill Coombs Robin Knight	BARC BARC BARC 750 Motor Club

Any three of the above may reach a decision

### 1.3 Competitor Eligibility:

- 1.3.1 Entrants where applicable must be in possession of a valid 2008 MSA Entrants Licence.
- 1.3.2 Drivers must be fully paid up valid 'racing membership' card holding members of the CTCRC and the BARC be Registered for the Championship and be in possession of a valid MSA Competition (Racing) National B Licence or higher.
- 1.3.3 All necessary documentation must be presented for checking at all rounds when signing-on.

### 1.4 Registration:

- 1.4.1 All drivers must register as competitors for the championship by returning the Registration form to the Championship Co-ordinator a minimum of 7 days prior to the Final Closing date for the first round being entered. Championship points will only be awarded to competitors who have fully complied with this regulation.
- 1.4.2 Alternatively, competitors may register 'on line' by visiting the BARC website at [www.barc.net](http://www.barc.net). When registering on line competitors should NOT complete and submit the paper version of the registration form (section 7).
- 1.4.3 The Registration Fee is FREE
- 1.4.4 Registrations will be accepted from 1st January 2008 until further notice.
- 1.4.5 Registration numbers will be the permanent Competition numbers for the Championship. Each registered driver will be allocated a permanent number for the season by the CTCRC Registrar in consultation with the Championship Co-ordinator and these will be issued strictly on receipt of a fully completed registration form.
- 1.4.6 Official Championship Registration Cards will be issued by the BARC only on receipt of the attached Registration Form.

## 1.5 Championship Rounds:

The 2008 BARC / CTCRC PRE 1993 TOURING CAR CHAMPIONSHIP will be contested over 12 rounds as follows:

Round:	Date:	Circuit	Organising Club/Centre
1	24 March 2008	Castle Combe	CCRC
2	12 April 2008	Lydden Hill	BARC SE
3	26-27 April 2008	Snetterton	BARC
4	18 May 2008	Mallory Park	BARC
5	21 June 2008	Oulton Park	BARC NW
6 / 7	19-20 July 2008	Croft	BARC
8	02-03 August 2008	Donington Park	BARC
9	24-25 August 2008	Brands Hatch	BARC
10 / 11	13-14 September 2008	Pembrey	BARC
12	04-05 October 2008	Silverstone	BARC

1.5.1 **NOTE:** In accordance with MSA Regulation A29(c) the organisers reserve the right to amend the published list of dates and rounds, in which case, all registered competitors will be informed of the amendments by Official Bulletins posted to the competitor address specified on the Official Registration Form, as soon as is practically possible.

## 1.6 Scoring:

1.6.1 Points will be awarded to Competitors listed as classified finishers in the Final Results as follows:-

Position	4 or more Starters	3 Starters	2 starters	1 starter
1st	9	9	8	7
2nd	6	6	5	-
3rd	4	4	-	-
4th	3	-	-	-
5th	2	-	-	-
6th	1	-	-	-

1 additional point will be awarded to each competitor who starts from the grid.

1 additional point will be awarded for fastest lap in each class except when there is only one starter in the class unless a new lap record is set.

In the event of a tie for positions for fastest lap competitors will be awarded equal points

1.6.2 The totals from all qualifying rounds **less 2** will determine final championship points and positions.

1.6.3 Ties shall be resolved using the formula in Regulation G11. of the 2008 MSA Yearbook.

1.6.4 The Classic Touring Car Racing Club will administer a team award within this Championship. A team entry comprises one car driven by more than one driver and must be registered as such with the CTCRC Registrar before it's second race of the season. Each team driver must independently comply with the eligibility criteria of Regulation 1.3.2. Only points earned after the teams registration will count towards the team award. A team may revert to individual drivers at any time during the season.

## 1.7 Awards:

1.7.1 All awards are to be provided by the BARC

1.7.2 Per Round: Trophy to Winner and Trophy to other class winners

1.7.3 Presentations:  
Garlands and Trophies are to be provided for presentation at the end of each race or at an end of the meeting presentation ceremony. Prizemoney and Bonuses shall be posted to the Entrants within 28 days of the results being declared final after each round.

1.7.4 Entertainment Tax Liability. Not Applicable.

- 1.7.5 Title to all Trophies:  
In the event of any Provisional Results or Championship Tables being revised after any provisional presentations and such revisions affect the distribution of any awards the Competitors concerned must return such awards to the BARC in good condition within 7 days.

## **2. SPORTING REGULATIONS - JUDICIAL PROCEDURES**

- 2.1 Rounds:** In accordance with Section C(d) of the 2008 MSA Yearbook and these Regulations.
- 2.2 Championship:** In accordance with Section C(d) of the 2008 MSA Yearbook and these Regulations.

## **3. SPORTING REGULATIONS – CHAMPIONSHIP RACE MEETINGS & RACE PROCEDURES**

### **3.1 Entries:**

- 3.1.1 Competitors are responsible for sending in correct and complete entries with the correct entry fees prior to the entry closing dates which shall be 20 days before each round.
- 3.1.2 In correct or incomplete entries (Including Driver to be Nominated Entries) are to be held in abeyance until they are complete and correct and the date of receipt for acceptance of entry purposes shall be the date on which the Secretary of the Meeting receives the missing or corrected information or fee.
- 3.1.3 Any withdrawal of Entry or Driver/Car changes made after acceptance of any entry must be notified to the Secretary of the Meeting in writing. If Driver/Vehicle changes are made after publication of Entry Lists with Final Instructions the Competitor concerned must apply for approval of acceptance by the Stewards of the Meeting **BEFORE** signing-on.
- 3.1.4 The Maximum Entry Fee for each round shall be: as per Supplementary Regulations for the event.
- 3.1.5 There is no provision for Qualification races.
- 3.1.6 Reserves are to be nominated on the Final List of Entries published with Final Instructions or Amendment Sheet Bulletins. All Reserves will practice and replace withdrawn or retired entries Reserve Number order irrespective of class. If Reserves are given Grid Places prior to issue of the first Grid Sheets for any round the times set in Practice shall determine their grid positions. If Reserves are given places after publication of the grid sheet and prior to cars being collected in Official "Assembly Areas" they will be placed at the rear of the Grid and be started without any time delay. Otherwise, they will be held in the Pitlane and be released to start the race after the last car to start the **GREEN FLAG LAP** or last car to take the start has passed the startline or pitlane exit, whichever is the later. Such approval to start **MUST** be obtained from the Clerk of the Course.

### **3.2 Briefings:**

Organisers should notify Competitors of the times and locations for all briefings in the Final Instructions for the meetings. Competitors must attend all briefings.

### **3.3 Practice:**

- 3.3.1 The minimum period of practice to be provided is to be as specified in the MSA Regulations in respect of the circuit lengths.
- 3.3.2 Should any Practice Session be disrupted the Clerk of the Course shall not be obliged to resume the session or re-run sessions to achieve the championship criteria and the decision of the Clerk of the Course shall be final.

- 3.3.3 For races marked ( D/Header) in section 1.5., where it is planned to hold two championship races, there shall be a single qualifying session as per 3.3.1. above. The result of the first race will set the grid for the second race. DNF's from race 1 can start from the back of the grid in race 2 in reverse order of retirement.

### 3.4 Qualification:

Each driver should complete a minimum of 3 laps practice in the car to be raced and in the correct session in order to qualify for selection and order of precedence as set out in the MSA Regulation G15. The Clerk of the Course and/or Stewards of the Meeting shall have the right to exclude any driver whose practice times or driving are considered to be unsatisfactory - as per MSA Regulation G15.

### 3.5 Races:

The standard minimum scheduled distance shall be 12 miles whenever practicable but should any race distance be reduced at the discretion of the Clerk of the Course or Stewards of the Meeting it shall still count as full points scoring round.

### 3.6 Starts:

- 3.6.1 All race start countdowns are to have a minimum elapsed period of 5 minutes from the time all cars are released to form up on the grid to the start of the Green flag Lap(s) in the formation as specified on the Track Licence for each circuit.
- 3.6.2 The Countdown procedures/audible warnings sequence shall be: Standing Starts:-  
3 minutes to start of Green Flag/Pace Lap - Close Pitlane Exit.  
2 minutes to start of Green Flag/Pace Lap - Clear Grid Warning/Grid Closed.  
1 minute to start of Green Flag/Pace lap - Start engines/Clear Grid.  
30 seconds - Visible and audible warning for start of Green Flag/Pace Lap.
- 3.6.3 The use of tyre heating/heat retention devices, tyre treatments and compounds is prohibited.
- 3.6.4 Any cars removed from the grid after the 3 minute stage or driven into pits on Green Flag lap shall be held in the pitlane and may start the race after the last car to take the start from the grid has passed the startline or pitlane exit. whichever is the later.
- 3.6.5 Any drivers unable to start the Green Flag/Pace lap or start are required to indicate their situation as per MSA Regulation G53 and any drivers unable to maintain grid positions on the Green Flag Lap to the extent that **ALL** other cars are ahead of them, may complete the Green Flag lap but **MUST** remain at the rear of the last row of the grid but ahead of any cars to be started with a time delay.
- 3.6.6 Excessive weaving to warm-up tyres - using more than 50% of the track width, and falling back in order to accelerate and practice starts, is prohibited.
- 3.6.7 A five second board will be used to indicate that the grid is complete. The red lights will be switched on five seconds after the board is withdrawn.

In the event of any starting lights failure the Starter will revert to the use of the National Flag.

### 3.7 Race Stops:

- 3.7.1 Should the need arise to stop any race or practice, **RED LIGHTS** will be switched on at the Startline and **RED FLAGS** will be displayed at the Startline and at all Marshals Signalling Points around the Circuit.
- This is the signal for all drivers to cease circulating at racing speeds, to slow to a safe and reasonable pace and to return to the starting grid area which will automatically become a Parc Ferme area.
- Cars may not enter the Pits unless directed to do so. Work on cars already in the Pits must cease when a race is stopped.
- 3.7.2 Case A - Less than two laps completed by Race Leader:
- The race will be null and void. The race will restart from the original grid positions. Competitors unable to take the restart may be replaced by reserves who will start from the back in reserve order. Gaps on the grid should not be closed up. The length of the restarted race will be determined by the Clerk of the Course.

3.7.3 Case B - More than two laps completed by Race Leader but less than 50% of race distance:

The race will restart from a grid set out by the finishing order of part one. The result of the race will be the finishing order at the end of part two. The length of the restarted race will be determined by the Clerk of the Course.

3.7.4 If the leader has completed more than 50% of the race distance or duration it shall not be re-started and the results will be declared in accordance with MSA Regulation G23.

**3.8 Re- Scrutiny:**

All vehicles reported involved in contact incidents during races or practice must be re-presented to the Scrutineers before continuing in the races or practice.

**3.9 Pits & Pitlane Safety:**

3.9.1 Pits: Entrants must ensure that the MSA, Circuit Management and Organising Club Safety Regulations are complied with at all times.

3.9.2 Pitlane: The outer lane or lanes are to be kept unobstructed to allow safe passage of cars at all times. The onus shall be on all Drivers to take all due care and drive at minimum speeds in pitlanes.

3.9.3 Refuelling: May only be carried out in accordance with the MSA Regulations G67-70, Circuit Management Regulations and the SR's or Final Instructions issued for each Circuit/Meeting.

**3.10 Race Finishes:**

After taking the Chequered Flag drivers are required to: Progressively and safely slow down, remain behind any competitors ahead of them, return to the Pit Lane Entrance/Paddock Entrance as instructed, comply with any directions given by Marshals or Officials and to keep the helmets on and harnesses done up while on the circuit or in the pitlane.

**3.11 Results:**

All Practice Timesheets, Grids, Race Results are to be deemed **PROVISIONAL** until all vehicles are released by SCRUTINEERS after Post Practice/Race Scrutineering and/or after completion of any Judicial or Technical Procedures.

**3.12 Timing Modules:**

3.12.1 All competitors will be required to fit an Electronic Self Identification Module (Transponder) to their car for the purposes of accurate timing. Holders for these and detailed fitting instructions will be issued with the transponders and it will be the responsibility of the competitor to fit these in the car in the position and manner specified. The Modules must be in place and functioning correctly for all Championship qualifying practice sessions and races. The setting and servicing of these items must only be carried out by properly authorised MSA licensed Timekeepers. Competitors will be charged by the timing company for replacement of the Modules due to misuse or loss at any time during the season.

3.12.2 Competitors may not place electronic timing equipment within five metres of the official Start, Finish or any other official timing lines at any event or test session/day. Any such equipment placed within these zones will be removed.

**3.13 Safety Car:**

3.13 There is no provision for the use of a Safety Car at the events forming part of this Championship

## **4. CHAMPIONSHIP RACE PENALTIES:**

### **4.1 Infringements of Technical Regulations:**

4.1.1 Arising from post practice Scrutineering or Judicial Action:

Minimum Penalty: The provisions of MSA Regulations: C(d)36

4.1.2 Arising from post race Scrutineering or Judicial Action:

Minimum Penalty: The provisions of MSA Regulations: C(d)39 (a) and (b).

For infringements deemed to be of a more serious nature the Clerk of the Course and/or Stewards of the Meeting are to invoke the provisions of Regulation C(d)39 (c)

4.1.3 Additional specific championship penalties: At the discretion of the Championship Stewards.

4.1.4 Any competitor found guilty of contravening these Regulations (Sporting or Technical) may be reported to the Stewards of the Championship for possible imposition of further penalties which may include total exclusion from the Championship.

### **4.2 Infringements of non-technical MSA Regulations and the Sporting Regulations issued for the Championship:**

As per 2008 MSA Judicial Procedure Regulations.

# 2008 TRACK & RACE CAR PRE 1993 TOURING CAR CHAMPIONSHIP

## 5. TECHNICAL

### 5.1 Introduction:

The following technical regulations are set out in accordance with MSA specified format and it should be clearly understood that if the following texts do not clearly state that you can do it, you should adopt the principal that you cannot.

### 5.2 Description:

5.2.1 "Pre 1993 Touring Cars" are two wheel drive four seater saloon cars marketed before 1st January 1993, of which more than 5000 examples were manufactured in any 12 month period during the overall production run and/or were homologated by F.I.A. for competition in Group N category for production cars, prior to that date. All cars are subject to approval of eligibility by the CTCRC Committee and cars not complying with these regulations may be eligible subject to CTCRC Committee approval.

Cars complying with BARC/CTCRC Group One Touring Car regulations are also eligible except they may run wheels and tyres in accordance with regulation 5.12 of these Pre'93 regulations..

Cars entered in Class F Production BMW are subject entirely to regulations of section 5a and not otherwise.

The responsibility to prove eligibility is that of the entrant at all times. For clarification of an entrant refer to the MSA Yearbook C(a)3. All entrants must produce HVIF / Homologation papers stamped by the ASN, where issued for that vehicle and these must be available for inspection at scrutineering. Where no such paperwork is available, the entrant must produce written confirmation from the CTCRC Committee as to the eligibility of the vehicle model in question. The CTCRC Committee in conjunction with the Championship Eligibility Scrutineer shall determine matters as to the eligibility and the implementation which may involve photographing any part of the vehicle and performing electrical diagnostics at the scrutineer's discretion.

5.2.2 Unless specifically permitted in these regulations, all components must be to original specification.

5.2.2 Cars will run in five classes based on production capacity:

Class A	Over 3900cc
Class B	2501cc to 3900cc
Class C	2001cc to 2500cc
Class D	1601cc to 2000cc
Class E	Up to 1600cc
Class F	Production BMW

The following rules will also be applied;

- Forced induction engines with 4 valves per cylinder are subject to an equivalency factor of 1.7
- Forced induction engines with 2 valves per cylinder are subject to an equivalency factor of 1.4
- Rotary engines are subject to an equivalency factor of 2
- Naturally aspirated cars 2000cc and over, with 2 valves per cylinder are subject to an equivalency factor of 0.8.

The Ford Cosworth Sierra must run with an intake restrictor of 36mm.

Cars with a number of injectors in excess of the number of cylinders are not eligible for this championship. The E36 M3 EVO, Nissan Skyline and Escort Cosworth or components homologated for these vehicles are not eligible for this championship.

5.2.4 Cars must be presented to a high standard.

5.2.5 Presentation for a vehicle for scrutineering is a declaration by the entrant that the vehicle is eligible for that event.

### **5.3 Safety Requirements:**

All vehicles regardless of engine capacity must be fitted with a full rollcage to a minimum of MSA Yearbook drawing C(c)69-71 or C(c)72-73 and safety doorbars are mandatory. All vehicles must comply with the minimum prevailing MSA safety requirements.

### **5.4 Miscellaneous:**

- 5.4.1 Vehicles may be brought up to any series production specifications for that model prior to 1st January 1993.
- 5.4.2 Competitors registering in this Championship do so in the full knowledge that CTCRC reserves the right to require the Championship Eligibility Scrutineer to carry out, record and enforce eligibility checks which may include the sealing of component(s) for subsequent checking. The costs of such checking shall be borne by the CTCRC but the CTCRC shall not be liable for the costs of stripping or reassembly or rebuilding of vehicles after the checks have been carried out.
- 5.4.3 Where these regulations call for original components or pattern parts these must be to the manufacturers original specifications for that model as catalogued by the manufacturer or importer prior to 1st January 1993.
- 5.4.4 Advertising on vehicles is subject to requirements set out in MSA Yearbook C(a)55.
- 5.4.5 All vehicles must comply with MSA General Technical Regulations and the relevant parts of sections C(b) & G of the MSA Yearbook except where specified below.
- 5.4.6 Any component listed on the MSA or FIA (or national equivalent for foreign cars) homologation papers for use in Group 'N' during the series production of that model may be substituted for the original production component, save that no component may be substituted which serves to alter the shape or size of the bodyshell and/or panels themselves or increases the capacity of the engine beyond that which was in production or homologated prior to 1st January 1993. Optional equipment is to be submitted to the CTCRC committee for possible inclusion on a vehicle by vehicle basis. The responsibility to prove eligibility is that of the entrant at all times as set out in 5.2.1.
- 5.4.7 Nuts, bolts, washers and locking devices are free.
- 5.4.8 Vehicles must be fitted with at least one externally mounted rear view mirror.
- 5.4.9 Engines may be sealed at any time by a Licensed Eligibility Scrutineer and only by written permission in advance from the CTCRC Committee or a Licensed Eligibility Scrutineer may seals be broken.

### **5.5 Chassis:**

- 5.5.1 Chassis and chassis members must remain as originally manufactured and lightening or reducing of chassis or chassis member strength is prohibited.
- 5.5.2 Addition of material to strengthen the chassis and seam welding is permitted.
- 5.5.3 Minimum ground clearance is 60mm.
- 5.5.4 Steering wheels and steering columns are free.
- 5.5.5 Foot controls and their linkages are free except that the foot operated surface of the brake pedal must be located no more than 4" forward or rearward of the original production position.

### **5.6 Bodywork:**

- 5.6.1 Bodywork must be complete and standard in shape and silhouette, material and thickness on all exterior surfaces except that bonnets, boots and spoilers may be replaced with fibreglass replicas and any non metallic panel may be replaced with a fibreglass replica. The original steel bonnet or boot may be modified to reduce its weight providing that the visible exterior surface remains as manufactured. Where original materials are unobtainable, local repairs of adequate strength may be made using modern equivalents. Replacement of panels with non-original material is otherwise prohibited. The removal of exterior decorative strips and bumper overrides is permitted. Reworking or modification to exterior bodywork is prohibited but any part of the arch/wing pressing folded into the wheel arch may be deformed, but not removed, to give clearance to the tyres.

All internal panels and subassemblies must remain as originally manufactured. Strengthening is permitted. Battery trays and their supports may be removed. It is only permitted to make holes in panels for the passage of cables, fuel, water, oil, hydraulic, instrument or fire extinguisher lines.

#### 5.6.3 Interior:

a) These regulations require the retention of the dashboard and interior door trim in original or other non-flammable material. In the habitacle, floor carpets, under felt, sound deadening, headlining, front and rear parcel shelves, centre consoles, the front passenger and rear seats and trim in the boot/luggage compartment may be removed.

b) Instrumentation is free.

c) All window winder mechanisms must be fully operational and function as production. It is permissible to change electrically operated windows to manual winding operation. Windows must be of the same material as production.

d) Driver's seat is free subject to MSA requirements and the driver must be located entirely to one side of the centre line of the car.

e) Heaters and interior ventilation systems may be removed.

5.6.4 The original boot and bonnet hinges and fasteners may be removed and are free but the original bonnet and boot shut lines must be as in production.

### 5.7 Engine:

5.7.1 The engine must be located in the original position.

5.7.2 The original standard production cylinder block may be used or an alternative manufactured by the same manufacturer to the original production specification including but not limited to material, bore, number of main bearings and number of main bearing fasteners must be used and may be re-bored up to a maximum of plus 0.065".

5.7.3 The cylinder head(s) must be the standard production component or an alternative manufactured by the same manufacturer as the original production component to original production specification including but not limited to material, number of valves, ports and plugs, same plug angle, valve angle/port configuration and operating type and fixes directly onto the original standard production cylinder block without modification.

5.7.4 The crankshaft is free, but the original stroke and number of bearings must be retained.

5.7.5 Camshafts, camshaft bearings and drive systems are free, provided that they remain in their original positions and remain the sole means of operating the valves.

5.7.6 Induction. The original production type of induction only is permitted except that vehicles fitted with injection in production may be converted to carburettors if another eligible variant of the same model sharing the same bodyshell was also available with a carburettor equipped engine. The number of chokes of the replacement carburettion must not exceed the number of chokes originally fitted to this carburettor equipped variant.

Inlet trumpets are not permitted to have automatically controlled adjustment.

Carburettors, their linkages and inlet manifolds are free, within the limitation that the total number of chokes must not exceed the maximum number of chokes homologated for Appendix 'J' Group N.

Fuel injection is only permitted if fitted in production or homologated prior to 1st January 1993 and must employ the original production method of triggering and operation. The plenum chamber is free but the number of throttles must not exceed the number fitted in production or homologated before 1<sup>st</sup> January 1993. The fuel injector nozzles must be in the original location and must not exceed the original number fitted in production or homologated before 1<sup>st</sup> January 1993.

Air filter and air filter box may be removed and air ducting/trunking is free provided it does not extend beyond the periphery of the bodywork. Anti surge pipes are permitted as also are return pipes from the carburettor/injection system.

5.7.7 Radiators are free but must remain in their original location.

- 5.7.8 Oil coolers and additional water radiators are permitted provided they are located within the periphery of the bodywork.
- 5.7.9 The exhaust system is free subject to MSA requirements.
- 5.7.10 Dry sump systems are prohibited.
- 5.7.11 The ignition system is free however the firing order must not be changed.
- 5.7.12 Forced induction is not permitted unless either fitted in production or homologated in F.I.A. Appendix 'J' Group N before 1st January 1993. Cars using forced induction with four valves per cylinder will be subject to an equivalency factor of 1.7:1. Cars using forced induction with two valves per cylinder will be subject to an equivalency factor of 1.4:1. Boost pressure must not be adjustable from within the habitacle. When fitting of a turbocharger is permitted by these Regulations it shall be the standard production or homologated component and must not be modified save for the fitting of a 360 degree thrust bearing to improve reliability. The boost pressure setting is free. Intercoolers may only be fitted if used in production and must be the standard production unit or that fitted to the Ford Sierra Cosworth 4x4.
- 5.7.13 Inlet and exhaust manifolds are free.
- 5.7.14 It is permissible to remove metal from original cylinder blocks and heads.
- 5.7.15 Rotary engine cars. The induction timing is free and therefore the dimension of the induction port which controls its opening and closing point may be modified by removal and addition of material. In all other respects the port must remain as homologated. The engine capacity will be determined by using an equivalency factor of 2:1
- 5.7.16 Fuel pumps and fuel tanks are free subject to MSA requirements.
- 5.7.17 All other engine components are free.
- 5.7.18 Engine Sealing: To allow for scrutineers wire seals, every installed engine must have 1/16" holes drilled in readily accessible locations:
  - A - Sump: Cross drilled through two adjacent retaining screws or studs.
  - B - Rocker/cam cover: Cross drilled through two adjacent retaining screws or studs.
- 5.7.19 All engines will be sealed at the car's first event.  
The seals must be in place at all times. If a seal needs to be removed for any reason, the entrant must inform the championship/series scrutineer who will then re-seal at the first opportunity.

## **5.8 Suspension:**

- 5.8.1 Suspension springs are free except for maintaining type (coil, leaf, torsion) and no more than the original number are employed. Spring caps are free and spring platforms may be adjustable. A telescopic damper may be converted to a coilover and redundant coil springs removed.
- 5.8.2 Suspension type must remain unaltered. The original suspension components (or pattern parts to the manufacturer's original specification) must be employed in their original positions but may be strengthened except that Track Control Arms may be modified locally solely for the purpose of adjusting length and this may be achieved by use of a track rod end joint at one end of the TCA. Macpherson Strut top mounts are free. The original suspension mounting points are to be used without modification but may be strengthened.
- 5.8.3 Dampers are free providing the original operating principle (hydraulic, friction, lever or telescopic) and no more than the original number are employed. These must be mounted on the original mounting points.
- 5.8.4 Anti roll bars and their mountings and shape and material are free providing they fit directly on to the original body/chassis mounting points and the mobile suspension units. No other additional suspension components are permitted.
- 5.8.5 Suspension bushes are free providing the original production bush can be replaced in it's original position without modification to the bush housing. It is permitted to machine circlip retaining grooves to locate suspension bushes.

## **5.9 Transmission:**

- 5.9.1 The gearbox must remain in the original position. Vehicles must use either the original production type of gearbox or the homologated alternative.
- Chevrolet Camaro IROC-Z may use a 4 or 5 speed manual gearbox from any other production Chevrolet Camaro, of or prior to the period.
- 5.9.2 Gear ratios and type are free but gearboxes and transaxles with rapidly interchangeable ratios or proprietary racing gearboxes are prohibited.
- 5.9.3 Only the original number of ratios and overdrives may be fitted.
- 5.9.4 The rear axle must remain in its original position.
- 5.9.5 The rear axle casing must be the original standard production component but may be locally modified.
- 5.9.6 The final drive ratio is free.
- 5.9.7 Mechanical limited slip or torque biasing differentials are permitted.
- 5.9.8 Sequential gearboxes and/or traction control devices are prohibited.
- 5.9.9. Where a differential casing is removable from an axle casing the differential casing must be regarded as part of the original axle casing and is covered by the same technical regulations.

## **5.10 Electrical:**

- 5.10.1 Electrical equipment is free provided that a generator, battery and starter are fitted and in full working order at all times.
- 5.10.2 Headlights, tail lights, stop lights, high intensity rear light and windscreen wiper to MSA requirements must be fitted and in full working order.

## **5.11 Brakes:**

- 5.11.1 Brake systems are free save that carbon disks and ABS systems are prohibited unless fitted in production in which case they must be to production specification. Ducting for the purpose of cooling brakes or removing dust is permitted provided it is not visible outside the car and serves no other purpose and if beneath the car does not project beyond a line drawn at 45 degrees to the horizontal and tangential to the bodywork (not including overriders). Modification or removal of brake back plates is permitted.
- 5.11.2 Cars must be fitted with an operational hand brake. Cars fitted with dual circuit braking are not required to have a handbrake fitted.
- 5.11.3 Brake lights must be operational and operated only by the brake pedal without a delay. The high intensity rear light must not be operated by the brake pedal.

## **5.12 Wheels and Tyres:**

### **5.12.1 Wheels:**

Road wheels must be no greater diameter than the original diameter plus 2" to a maximum of 18", fastened to their hubs by the original number of studs/bolts. Centre locking wheels and their hubs are prohibited. Material is free.

However, an original diameter wheel must be able to be fitted to the hub, as and when required. This effectively precludes the fitting of brake systems which are a larger diameter than the original wheels will allow. Competitors must supply an original diameter wheel on request.

Maximum permitted rim widths are:

Class A 9.0"

Class B 9.0"

Class C 8.0"

Class D 7.0"

#### 5.12.2 Tyres

The control tyre for the championship is the Toyo Proxes R888 (2G Compound only).  
Dunlop Formula 'R' D84J tyres are also eligible.  
No modification to tread pattern or depth is permitted.

### 5.15 Weights:

Minimum weights

Cars marketed after 1<sup>st</sup> January 1983 - the published Kerb weight minus 10%. This includes the driver, normally seated with racing overalls and helmet only.

Cars marketed before 1<sup>st</sup> January 1983 – at the weight determined by the CTCRC Group One Touring Car championship regulations.

Kerb weights will be determined by committee sourced reference material. The committee's decision is final. These are true minimum weights with no tolerance and all cars must comply at all times. Ballast is permitted to achieve these minimum weights but weight may only be removed within the limits of the modifications detailed within these regulations. Ballast must be securely attached within the habitacle and attachment bolts predrilled for the purpose of attaching scrutineers wire seals. The total weight of ballast carried, must be declared in the scrutineering log book and be in position at all times during practice and racing. All cars must comply with these weight limits irrespective of the year of manufacture and any other championship regulations or waivers.

### 5.17 Numbers and Championship Decals:

- 5.17.1 Only competition numbers as allocated by the CTCRC Registrar shall be displayed in accordance with MSA regulation C(b)6 and shall remain as allocated until the end of the season in question.
- 5.17.2 Wherever possible, all vehicles must display the current CTCRC issued number roundels without modification, the BARC Shield and any other advertising material associated with a Championship sponsor as required by the CTCRC. Failure to comply may result in exclusion from practice, race and/or results

## **5a. SPECIFIC TECHNICAL REGULATIONS FOR CLASS F: PRODUCTION BMW**

### **5a.1. CLASSES:**

There is a single class for the BMW E30 2 door coupe, 4 door saloon, 5-door estate ('Touring') or Convertible (for the avoidance of doubt, NOT Baur Cabriolet) BMW vehicles designated 318i and 320i with either the four cylinder eight valve M40 engine or the six cylinder M20 engine.

Should one particular model prove to have unequal performance, the CTCRC Committee reserves the right to review data a maximum of three times during the championship season and to introduce performance equalising measures accordingly with a minimum of 14 days notice to the MSA and competitors concerned. These measures may involve the fitting of additional weight or performance controlling equipment to either one or all of the models.

### **5a.2. GENERAL DESCRIPTION:**

5a.2.1 The championship is for BMW E30 series cars running either the 8 valve 1.8 litre four cylinder engine, designated M40 or the 2.0 litre six cylinder engines designated M20 as supplied fitted to the 318i and 320i models respectively. These models must have been produced in Germany for sale to the general public as shown in sales brochures and obtained through the European BMW dealer network.

The class is intended to provide close racing between drivers and not a technical challenge for preparation experts. The intention of the technical regulations is to create a car that is as safe as possible, fun to drive and yet remain as close to standard as possible. If you are contemplating any modifications about which you are unsure, you should call upon the CTCRC Committee for a decision. Competitors should assume that unless a modification is specifically permitted, that any modification is prohibited.

All competing vehicles shall be road legal and be capable of passing an MOT test at the beginning of each qualification or race entered. Insurance for road use, road fund licence and an MOT certificate are not required.

5a.2.2 Cars must be presented to a high standard. Excessive corrosion, poor paintwork or significant bodywork damage will incur a non compliance, which may result in exclusion from the practice / race / event entered.

### **5a.3. SAFETY REQUIREMENTS:**

5a.3.1 All MSA Appendix C(c) Safety Criteria Regulations apply as relevant and the following;

- i) A suitable FIA approved competition seat with integral lateral head restraints designed for use with a six-point harness and with appropriate mountings must be fitted according to regulation C(c)50 (G125)
- ii) A suitable harness of six-point design and carrying an FIA approved label must be fitted according to regulations C(c)45 Six Point
- iii) The use of an approved HANS device is recommended. To ensure correct fitment, please refer to the document published by the FIA Institute for Motor Sport Safety entitled "Guide for the use of HANS in international motor sport".
- iv) A plumbed-in fire extinguisher is required as detailed in regulation C(c)58-65 (G130) of minimum capacity 3.5 litres.
- v) A suitable Rollcage must be fitted, meeting the requirements set out below.

5a.3.2 The following criteria must be met for rollcage design and installation, with the exception of 5a.3.2 v which is optional.

- i) The rollcage design, construction and installation must satisfy all of C(c)4 - 6.
- ii) The rollcage material must be of cold drawn seamless carbon steel only.
- iii) Side intrusion Doorbars must be fitted and in accordance with C(c)20 and optionally C(c)24.
- iv) 6-point rollcages must include at least one reinforcement member as described in C(c)19.
- v) Triangulation between the rollcage front legs and front strut towers is permitted.

### **5a.4. GENERAL TECHNICAL REQUIREMENTS & EXCEPTIONS**

5a.4.1 Cars must fully comply with all relevant requirements of the 2008 MSA Year Book sections C(b) and G and these regulations.

- 5a.4.2 In respect to front towing eye, this may not protrude beyond the vertical plane of the front bumper by more than 10mm. For the avoidance of doubt this precludes the use of the standard towing eye in its standard location, competitors must find an alternative.
- 5a.4.3 One or more wide angle mirrors must be fitted to the standard wing mirrors or rear view mirror in order to cover the car's blind spots.
- 5a.4.4 To allow for scrutineers' wire seals, every installed engine must have 1.6mm holes drilled in at least two adjacent sump bolts and two adjacent rocker/cam cover bolts.
- 5a.4.5 All engines will be sealed at the car's first event. The seals must be in place at all times. If a seal needs to be removed for any reason, the entrant must inform the championship scrutineer who will then re-seal at the first opportunity.
- 5a.4.6 To facilitate technical scrutineering, engines will frequently be power tested with a handheld dynamometer, known as a Schrick meter and operated in accordance with the manufacturer instructions . In order to assist this process, all competing cars must be fitted with a standard electrical connection to operate the device.

Schrack connectors and fitting instruction are available on request from the CTCRC Committee.

### 5a.5. CHASSIS:

The construction type, design and material must remain as standard. Lightening or reducing the chassis strength is prohibited. Additional strengthening of the chassis is prohibited (e.g. seam welding). The chassis as produced by the manufacturer with the original material must be retained in all aspects in respect of material, thickness & contour. For the benefit of doubt, chassis is defined here to include the body shell, wings, doors, bonnet, boot-lid, roof and panels.

### 5a.6. BODYWORK:

As per MSA regulation C(b)8(k) apply as relevant

#### 5a.6.1 Modifications permitted but not mandated

- i) All sound proofing and heat shielding material may be removed
- ii) Mechanically operated items may replace electrically operated items provided that the substituted mechanical parts were available on the 318i/320i E30 models. It is not permitted to replace an electrically operated part with a non-standard alternative mechanical part or mechanism.
- iii) Sunroof mechanisms can be removed entirely. If the sunroof panel is removed it must be replaced with the same material and thickness as the roof skin (G129).
- iv) A strut brace between the front strut towers may be fitted.
- v) A strut brace between the rear strut towers may be fitted.
- vi) Items originally fitted as optional extras to the vehicle may be removed. This includes:
  - Cruise control
  - Air conditioning
  - Headlamp wash/wipe
  - Front fog lights
  - In-cabin headlamp height adjuster
- vii) The original engine undertray may be removed or replaced with a metal skid plate to protect the sump provided that the plate is not be more than 100mm wider than the sump and extends no further back than the front bulkhead.
- viii) A metal skid plate may be fitted to cover the fuel tank. The plate itself may not extend more than 100mm beyond the tank in any direction.
- ix) Door cards may be removed. If removed, they must be replaced with an alternative panel that protects the driver from sharp edges and the intrusion of metal structures in the event of a side impact.
- x) A boot spoiler may be fitted to the rearmost edge of the boot lid. This spoiler must be of the same material and dimensions as BMW part "HECKSPOILER TYP 1 916 038".
- xi) Number plates may be removed.
- xii) Headlamps may be covered with protective tape provided they are not coloured red.
- xiii) Front and rear windows may be covered with championship or personal sponsor livery to a maximum depth of 250mm from the top of the window, measured from the centerline of the vehicle and must also comply with G101.

- xiv) The rear bulkhead may be modified to accommodate the rollcage. Where holes have been cut to fit the rollcage they shall be no more than twice the diameter of the rollcage member to be fitted. All such holes shall be sealed after fitting the rollcage.
- xv) The bonnet catch mechanism may be replaced as per G105. Redundant bonnet hinges and support struts may be removed but refer to 5a.5.
- xvi) 4-door and estate models may remove the interior material and window mechanisms from the rear passenger doors.
- xvii) Estate models may remove the interior material and hinge mechanisms from the tailgate but refer to G105.
- xviii) The wheel arch liners may be removed and the inner lip of the wheel arch may be "rolled" to prevent fouling the tyre but no material may be removed.
- xix) All side window glass may be removed from convertible models

#### 5a.6.2 Interior

- i) All passenger seating must be removed. The driver's seat must be replaced as per 5a.3.1.i. The front passenger seat may be replaced with a competition seat, fitted as per C(c)50.
- ii) Any interior trim including dashboard trim, carpeting and sound proofing may be removed.
- iii) Window winding mechanisms, boot and door locks and catches must remain in place but can be disabled for safety reasons.
- iv) The dashboard may be modified to allow the fitting of the rollcage and the part of it to the left of the centre console (i.e. the glove box area) may be removed provided the dash is securely fitted and has suitable alternative supports. Windscreen vents must remain to allow demisting. Driver and passenger facing vents may be removed.

#### 5a.6.3 Modifications prohibited:

Refer to section 5a.2. The following examples are for the avoidance of doubt.

- i) Silhouette must remain standard. All spoilers, dams, splitters, aerofoils and diffusers are prohibited other than that mentioned in 5a.6.1.x.
- ii) All window glass must be retained as originally fitted except where allowed by 5a.6.1 xix. If nets are used to cover open side windows then the glass must still be retained.
- iii) Material, thickness and profile of external body panels may not be changed.
- iv) Plan must be as standard with no extensions to wheel arches permitted.
- v) The use of any undertrays, diffusers or any other aerodynamic device fitted to the underside of the vehicle, other than those fitted as standard, is prohibited but refer to 5a.6.1.vii and 5a.6.1.viii.
- vi) All bumpers must remain in complete condition. Bumper dampers, filling and all bumper mounting points must be retained.

Competitors are reminded that cars must be capable of passing an MOT test with the exceptions of modifications permitted by 5a.6.1 and 5a.13. "Write-off" cars are permitted so long as they are capable of passing the MOT roadworthiness test. A current MOT certificate is not required.

#### 5a.7 ENGINE:

As per MSA regulations C(b)10, C(b)16, C(b)18, C(b)19, C(b)22 and the following.

- i) Only the 8-valve, four-cylinder engine (designated M40) or the six-cylinder engine (designated M20) fitted to the BMW E30 318i or 320i models are eligible. For the avoidance of doubt, the 16-valve 318iS engine (designated M42) is not eligible.
- ii) No modifications to the engine or any ancillaries, including the fuel (except fuel pump [5a.15 v]), ignition systems or ECU are permitted. For the benefit of doubt, the engine must retain the standard specification block, pistons, con-rods, cylinder head, camshafts, valves, fuel pressure regulator and fuel rail.
- iii) Cleaning and decoking of the cylinder head is permitted but polishing, machining or any other modifications are prohibited.
- iv) The induction system must retain the standard airflow meter and throttle body, but upstream of the airflow meter is free. No mechanically forced induction is allowed.
- v) The standard exhaust manifold must be retained and not modified in any way but the remainder of the system is unrestricted but refer to 5a.16.
- vi) The standard cooling fan shall be retained and no additional cooling fans are permitted.
- vii) The original radiator cowling may be removed but non-standard cowling is prohibited.
- viii) Coolant hose material is free and hoses may be modified to accommodate an additional temperature sender.

- ix) The standard sump may have baffles fitted to prevent oil starvation. No other sump modifications are permitted.
- x) An oil cooling system consisting of oil radiator, oil filter head and associated pipework may be fitted solely for the purpose of reducing engine oil temperature.
- xi) The maximum overbore piston diameter is 84.5mm for the 318i and 80.5mm for the 320i.
- xii) The cylinder head may be skimmed to a minimum height of 140.6mm for the 318i and 124.7mm for the 320i.
- xiii) For the avoidance of doubt, the 320i standard throttle body inlet aperture is 53mm diameter and airflow meter outlet aperture is 60mm diameter. The 318i standard throttle body inlet aperture is 58mm diameter and airflow meter outlet aperture is 65mm diameter.
- xiv) For the avoidance of doubt, the standard Bosch ECU model numbers are listed below:

280 000 310	261 200 163
986 261 705	261 200 172
280 000 328	261 200 179
986 261 713	261 200 381
280 000 318	280 001 301
986 261 708	986 261 820
280 000 330	280 001 309
986 261 714	986 261 823
261 200 157	

### 5a.8 SUSPENSIONS:

As per MSA regulation C(b)11 and the following;

#### 5a.8.1 Modifications permitted but not mandated

- i) Camber is free. The top mounts on the front struts may be modified, or new holes may be drilled on the top of the suspension tower to achieve a greater camber than available as standard. Adjustable camber plates may be fitted to the original mounts for the same purpose." A spherical bearing may replace the original on the top of the front strut..
- ii) Bush material is free provided it is not made entirely of metal (with the exception of 5a.8.1.i)
- iii) All bushes must be of standard dimensions except those at the rear of the front control arms. In addition, all bushes must use only the original mountings and brackets.
- iv) Anti roll bars other than the standard front fitment to the 318i/320i (18.5mm diameter) are not permitted.
- v) Springs are free provided that they are constructed of steel but refer to 5a.8.1.ix
- vi) Adjustable shock absorbers may be fitted provided that there is only one manual mechanical damping adjustment and that there are no remote reservoirs.
- vii) "Coilover" spring/damper units are permitted but refer to 5a.8.1.vi. Rear coilovers must retain the original rear spring platforms but no spring may be fitted on those platforms.
- viii) 51mm diameter strut cartridges as from the BMW E30 325i model may be used.
- ix) Ground clearance as measured from the lowest part of the car, including the exhaust system shall be no less than 40mm, whilst meeting minimum weight requirements as per 5a.14.i. No part of the vehicle shall touch the ground if a tyre becomes deflated.
- x) Shock absorber upper mounts may use spherical bearings but must retain the standard bodysell mounting points.

#### 5.8.1 Modifications prohibited

- i) Other than 5a.8.1.i no changes to suspension pick up points are permitted.
- ii) All suspension components will be of the same design and made of the same material as that on the standard vehicle save for those permitted by 5a.8.1.i) Specifically aluminium components may not be replaced by steel components (or visa versa) and no component may be replaced by any composite material or alloys that include any element of Titanium or Magnesium.
- iii) No alterations to suspension geometry are permitted, other than that available on the standard car and as per 5a.8.1.i
- iv) Rod ends or other spherical bearings are not permitted save for 5a.8.1.i and 5a.8.1.x.
- v) No rear anti roll bar is permitted.

### 5a.9 TRANSMISSIONS:

As per MSA regulation C(b)17 and the following

- i) Only gearboxes, clutch and differentials as supplied with approved engines in the E30 318i and 320i model ranges will be permitted, excluding the automatic transmission option.

- ii) Gear ratios must be as supplied with the gearbox in production form. For reference, the standard forward ratios are 3.72, 2.02, 1.32, 1.00, and 0.80.
- iii) Gearbox and differential mounting and location points must be retained and used as intended by the manufacturer.
- iv) The standard 318i/320i differential must be used, with a final drive ratio of 4.10:1. Limited slip differentials are prohibited.
- v) A "short shift" gear lever (BMW part number 25.11.7.527.252) may replace the standard item.

#### **5a.10. ELECTRICS:**

5a.10.1 As per MSA regulation C(b)20 and the following;

- i) The standard heater/demisting mechanism (including rear window demisting) shall be retained, not modified in any way and shall be in full working condition.
- ii) The battery size and type is free but must be capable of starting the car unassisted. The battery must remain in its original location unless prevented by 5a.3.2.v, in which case it may be relocated elsewhere within the engine compartment.
- iii) The standard battery clamp is inadequate and an alternative or additional battery clamp should be used.
- iv) The alternator must remain in its standard configuration and be operational at all times while the engine is running.
- v) No devices may be added or modified to provide any form of traction control, launch control or full-throttle gearshifts.
- vi) Electrical switches can only operate the function for which they were originally fitted into the car for and for no other purpose, with the exception of the key-operated ignition and starter switches which may be replaced by separate switches.

5a.10.2 Modification to any electrical system, other than re-routing wiring, is not permitted with the exception of electrical supply to fuel pumps. As per Bodywork above, electric mechanisms may be substituted by mechanical. Sunroof mechanisms can be removed. Controls may be repositioned where allowable trim modifications require it (e.g. electric window switches, light switches).

The following redundant electrical items and associated wiring may be removed:

- i) On-board computers
- ii) Interior courtesy lamps
- iii) Boot illumination
- iv) Glovebox illumination
- v) Electric window override (safety) switch
- vi) Electric mirror control switch, providing mirror adjustment is still available. If electric mirrors are retained, the control switch need not be permanently installed.
- vii) Front fog lamps and switchgear.
- viii) Speakers, radio, tape player, 'head unit' or other In Car Entertainment systems.

**5a.10.3** Engine electronic control units (ECU's) will periodically be exchanged between competing cars with the same engine type or for a standard reference ECU held by the organisers. ECU's must therefore have good access and be quickly removable.

#### **5a.11 BRAKES:**

The braking system shall be as standard as fitted to either 318i or 320i, as per MSA regulation C(b)12 and the following;

- i) Anti-lock braking systems (ABS) must be removed or disabled.
- ii) Brake pad and shoe material is free but dimensions to remain as original equipment.
- iii) Discs are free but must be one-piece construction, steel, of original diameter and use standard callipers.
- iv) Adding of ducting and removal of splash guards only are allowed to improve brake cooling but refer to 5a.6.1.
- v) Rear discs as per standard fitment to the BMW E30 325i or 318i/320i with optional ABS system are permitted but refer to 5a.11.1.ii and 5a.11.1.iii above.
- vi) No adjustment to the brake bias is permitted.
- vii) The standard flexible brake lines may be replaced with braided items.

#### **5a.12 WHEELS / STEERING:**

As per MSA regulations C(b)13-14 and the following;

- i) The steering system including rack, tie rods, steering arms, and column shall remain as standard
- ii) The steering wheel is free within MSA regulations.
- iii) Only steel or single piece aluminium alloy road wheels are permitted of 15" diameter, maximum width 7J, offset between ET 15 and ET 25. Tyres should not foul the body or chassis when the steering is turned under both static and dynamic suspension load.
- iv) No wheel spacers that affect maximum vehicle track are allowed.
- v) Wheel hubs may be fitted with studs to accept wheel nuts.
- vi) Power assisted steering may be disabled but refer to 5.12.i.
- vii) A spare wheel may be fitted in the original location and must be securely mounted.

**5a.13. TYRES:**

The control tyres for the championship are "Toyo Proxes R888" in 195/50R15 size (2G compound only). It is prohibited to alter the tread pattern of the tyres by cutting and the original tread pattern must remain visible at all times.

**5a.14. WEIGHTS:**

Weight are defined in one way:

As the whole vehicle, including all consumables and fluids, at the end of each qualification or race entered including the driver in full racing kit.

Different minimum weights apply for 318i and 320i models, regardless of body style. All cars must achieve minimum weight as defined below:

<b>318i</b>	1065kg	<b>320i</b>	1125kg
-------------	--------	-------------	--------

Cars may carry ballast, as per C(b)11, in order to achieve the minimum weights.

**5a.15. FUEL TANK/FUEL:**

As per MSA regulation C(b)19 where appropriate. The design and location of the fuel tank shall be as manufacturer's specification. Only pump fuel as defined by the Terminology Section of the 2008 MSA Year Book is permitted.

- i) Fuel Tank type - standard
- ii) Location - standard
- iii) Fuel - only pump fuel as defined by section P of the 2006 MSA Year Book.
- iv) A fuel tank guard may be fitted to the underside of the car as per 5a.6.1.viii
- v) Fuel pumps are free, subject to MSA requirements.

**5a.16. SILENCING:**

All vehicles shall conform to MSA regulation C(b)23 'section A' and with the restrictions enforced by the Road Traffic Act.

## **6. APPENDICES:**

### **6.1 Race Organising Clubs and Contacts:**

BARC, Thruxton Circuit, Andover, Hampshire SP11 8PN  
Tel: 01264 772696 Fax: 01264 773794

CTCRC Competition Secretary: David Howard  
Tel: ??

Drivers Representatives: David Howard / Tim Scott Andrews  
Tel: ??

CTCRC Membership Secretary  
Tel: 0870 321 2277

Eligibility Scrutineers:  
Dennis Bown, 34 Elvaston Road, North Wingfield, Chesterfield, Derby S42 5HH  
Tel: 01246 854366 - Do not telephone after 22.00 hrs.

Matthew Godber, 19 Newbridge Lane, Brimington, Chesterfield, Derbyshire S43 1LX  
Tel: 07751 647841 - Do not telephone after 22.00 hrs.

Please do not telephone after 10.00 pm.

### **6.2 Commercial Undertakings:**

None

### **6.3 Agreed Waivers:**

3rd Generation Chevrolet Camaro may use an aftermarket Torque Arm on the rear axle instead of the production item.

### **6.4 Log Books:**

A central logbook will be held by the eligibility scrutineers where specific eligibility infringements will be recorded and a copy issued to the entrant at scrutineering.

# 2008 TRACK & RACE CAR PRE 1993 TOURING CAR CHAMPIONSHIP

## 7. REGISTRATION FORM

Please complete in capital letters

NAME OF DRIVER: \_\_\_\_\_

ADDRESS: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_ POSTCODE: \_\_\_\_\_

TEL(DAY): \_\_\_\_\_ (EVE): \_\_\_\_\_

E MAIL ADDRESS: \_\_\_\_\_

AGE: \_\_\_\_\_ DATE OF BIRTH: \_\_\_\_\_

NATIONALITY: \_\_\_\_\_

COMPETITION LICENCE No: \_\_\_\_\_ GRADE: \_\_\_\_\_

BARC MEMBERSHIP No: (Compulsory) \_\_\_\_\_ Expiry: \_\_\_\_\_

CTCRC MEMBERSHIP No: \_\_\_\_\_ (Compulsory)

NAME OF ENTRANT: \_\_\_\_\_

ADDRESS: \_\_\_\_\_  
(if different from above)

\_\_\_\_\_

\_\_\_\_\_ POSTCODE: \_\_\_\_\_

TEL(DAY): \_\_\_\_\_ (EVE): \_\_\_\_\_

ALL CORRESPONDENCE SHOULD BE SENT TO: DRIVER  ENTRANT

CAR: \_\_\_\_\_ MODEL: \_\_\_\_\_ CC: \_\_\_\_\_

CLASS ENTERED: A  B  C  D  E  F

**PLEASE NOTE:** It is mandatory to be a member of the Classic Touring Car Racing Club before you register for the above championship.

**COMPETITION NUMBER:** ----- This will be allocated by the CTCRC.

**PLEASE COMPLETE REVERSE OF FORM**

SIGNATURE OF ENTRANT: \_\_\_\_\_  
(if different from Driver)

SIGNATURE OF DRIVER: \_\_\_\_\_

PREVIOUS RACING EXPERIENCE OF DRIVER: \_\_\_\_\_

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

-----  
TO BE COMPLETED BY ALL APPLICANTS:

I wish to register for the **2008 TRACK & RACE CAR PRE 1993 TOURING CAR CHAMPIONSHIP** and I declare that the information given above is correct. I understand that should the above information change in any way I will confirm details in writing to the BARC as detailed below.

SIGNED: \_\_\_\_\_ DATE: \_\_\_\_\_

ONCE FULLY COMPLETED THIS FORM SHOULD BE RETURNED TO:

**The British Automobile Racing Club, Thruxton Circuit, Andover, Hampshire. SP11 8PN.**

PRIOR TO THE FIRST RACE ENTERED

-----  
FOR OFFICIAL USE ONLY

REGISTRATION FEE - FREE

DATE RECEIVED:.....

DATE REGISTRATION CARD SENT:.....

COMPETITION NUMBER ALLOCATED:.....