

*D.Wheadon*

**Signed & Dated  
D.Wheadon – 20/2/26**



**ADRIAN FLUX**  
Insurance for the Individual

## 2026 Adrian Flux MGOC Championship



**Organised by:**

**The British Automobile Racing Club**

Thruxton Circuit, Andover, Hampshire, SP11 8PN

**PUBLISHED COPY**



## CONTENTS

<b>SPORTING REGULATIONS - GENERAL.....</b>	<b>5</b>
1.1 TITLE & JURISDICTION:.....	5
1.2 OFFICIALS:.....	5
1.3 COMPETITOR ELIGIBILITY:.....	5
1.4 REGISTRATION:.....	6
1.5 CHAMPIONSHIP EVENTS:.....	6
1.6 SCORING:.....	6
1.7 AWARDS:.....	7
<b>CHAMPIONSHIP EVENT MEETINGS &amp; RACE PROCEDURES.....</b>	<b>8</b>
2.1 ENTRIES:.....	8
2.2 BRIEFINGS:.....	8
2.3 QUALIFICATION PRACTICE:.....	8
2.4 RACES:.....	8
2.5 STARTS:.....	8
2.6 SESSION RED SIGNALS:.....	9
2.7 PITS, PADDOCK & PITLANE SAFETY:.....	9
2.8 RACE FINISHES:.....	9
2.9 RESULTS:.....	10
2.10 TIMING MODULES:.....	10
2.11 QUALIFICATION RACES:.....	10
2.12 OPERATION OF SAFETY CAR:.....	10
2.13 ONBOARD CAMERAS:.....	10
<b>SPECIFIC CHAMPIONSHIP REGULATIONS.....</b>	<b>11</b>
<b>PENALTIES.....</b>	<b>12</b>
<b>TECHNICAL REGULATIONS – CLASSIC CLASS.....</b>	<b>13</b>
5.1 INTRODUCTION:.....	13
5.2 GENERAL DESCRIPTION:.....	13
5.3 SAFETY REQUIREMENTS:.....	13
5.4 CHASSIS:.....	13
5.5 BODYWORK AND INTERIOR:.....	13
5.6 ENGINE:.....	14
5.7 COOLING:.....	15
5.8 CARBURETTORS AND INDUCTION SYSTEM:.....	16
5.9 EXHAUST SYSTEM:.....	16
5.10 IGNITION SYSTEM:.....	16
5.11 SUSPENSION:.....	16
5.12 TRANSMISSION AND FINAL DRIVE:.....	16
5.13 ELECTRICAL SYSTEMS:.....	17
5.14 BRAKES:.....	17
5.15 FUEL SYSTEM:.....	17
5.16 WHEELS/STEERING:.....	18
5.17 TYRES:.....	18
5.18 WEIGHTS:.....	18
5.19 NUMBERS AND CHAMPIONSHIP DECALS:.....	18
<b>TECHNICAL REGULATIONS – CLASS B.....</b>	<b>19</b>
6.1 INTRODUCTION:.....	19
6.2 GENERAL DESCRIPTION:.....	19
6.3 SAFETY REQUIREMENTS:.....	19
6.4 CHASSIS:.....	19
6.5 BODYWORK:.....	19
6.6 ENGINE:.....	20



6.7	COOLING SYSTEM: .....	20
6.8	INDUCTION SYSTEM:.....	21
6.9	EXHAUST SYSTEM: .....	21
6.10	IGNITION SYSTEM: .....	21
6.11	SUSPENSION: .....	21
6.12	TRANSMISSION: .....	21
6.13	ELECTRICAL SYSTEMS:.....	22
6.14	BRAKES:.....	22
6.15	WHEELS/STEERING: .....	22
6.16	TYRES: .....	22
6.17	WEIGHTS:.....	22
6.18	FUEL TANK/FUEL SYSTEM: .....	22
6.19	SILENCING:.....	22
6.20	NUMBERS AND CHAMPIONSHIP DECALS:.....	23
6.21	INTRODUCTION:.....	23
6.22	GENERAL DESCRIPTION:.....	23
6.23	BODYSHELL: .....	23
6.24	INTERIOR:.....	23
6.25	ENGINE: .....	24
6.26	COOLING SYSTEM: .....	25
6.27	INDUCTION SYSTEM:.....	25
6.28	EXHAUST SYSTEM: .....	25
6.29	IGNITION SYSTEM: .....	25
6.30	SUSPENSION: .....	25
6.31	TRANSMISSION: .....	26
6.32	ELECTRICAL SYSTEM: .....	26
6.33	BRAKES:.....	26
6.34	FUEL TANK/FUEL SYSTEM: .....	26
6.35	WHEELS/STEERING: .....	27
6.36	TYRES: .....	27
6.37	WEIGHTS:.....	27
6.38	NUMBERS AND CHAMPIONSHIP DECALS:.....	27
<b>TECHNICAL REGULATIONS – CLASS F.....</b>		<b>28</b>
7.1	INTRODUCTION:.....	28
7.2	GENERAL DESCRIPTION:.....	28
7.3	SAFETY REQUIREMENTS: .....	28
7.4	BODYSHELL: .....	28
7.5	INTERIOR:.....	29
7.6	ENGINE: .....	29
7.7	COOLING SYSTEM: .....	30
7.8	INDUCTION SYSTEM:.....	30
7.9	EXHAUST SYSTEM: .....	30
7.10	IGNITION SYSTEM: .....	30
7.11	SUSPENSION: .....	31
7.12	TRANSMISSION: .....	31
7.13	ELECTRICAL SYSTEMS:.....	32
7.14	BRAKES:.....	32
7.15	FUEL TANK/FUEL SYSTEM: .....	32
7.16	WHEELS/STEERING: .....	32
7.17	TYRES: .....	32
7.18	WEIGHTS:.....	33
7.19	NUMBERS AND CHAMPIONSHIP DECALS:.....	33
<b>TECHNICAL REGULATIONS – CLASS Z.....</b>		<b>34</b>



ADRIAN FLUX  
Insurance for the enthusiast



8.1	INTRODUCTION:.....	34
8.2	GENERAL DESCRIPTION:.....	34
8.3	SAFETY REQUIREMENTS: .....	34
8.4	BODYSHELL: .....	34
8.5	INTERIOR:.....	35
8.6	ENGINE: .....	35
8.7	COOLING SYSTEM: .....	36
8.8	INDUCTION SYSTEM:.....	36
8.9	EXHAUST SYSTEM: .....	36
8.10	IGNITION SYSTEM: .....	36
8.11	SUSPENSION: .....	37
8.12	TRANSMISSION: .....	37
8.13	ELECTRICAL SYSTEMS:.....	38
8.14	BRAKES:.....	38
8.15	FUEL TANK/FUEL SYSTEM: .....	38
8.16	WHEELS/STEERING: .....	38
8.17	TYRES: .....	38
8.18	WEIGHTS:.....	39
8.19	NUMBERS AND CHAMPIONSHIP DECALS:.....	39
<b>TECHNICAL REGULATIONS – CLASS I: INVITATION CLASS.....</b>		<b>40</b>
9.1	INTRODUCTION:.....	40
9.2	TYRES: .....	40
9.3	NUMBERS AND CHAMPIONSHIP DECALS:.....	40
<b>APPENDICES .....</b>		<b>41</b>
10.1	MGOC CONDUCT AND DRIVING STANDARDS:.....	41
10.2	RACE ORGANISING CLUB & CONTACTS:.....	41
<b>APPENDIX – RACE WITH RESPECT.....</b>		<b>42</b>
<b>REGISTRATION FORM .....</b>		<b>43</b>

BARC Championships support Motorsport UK and the Race With Respect campaign. By registering to compete you agree to respect the code of conduct. This way everyone can race in a safe, welcoming and fair environment. #RaceWithRespect



## 1. SPORTING REGULATIONS - GENERAL

### 1.1 TITLE & JURISDICTION:

The Adrian Flux MGOC Championship is organised and administered by the British Automobile Racing Club (BARC) and promoted by them, in accordance with the National Competition Rules of Motorsport UK (incorporating the provisions of the International Sporting Code of the FIA) and these Championship Regulations.

Motorsport UK Championship Permit No:	CHR2026/R044
Race Status:	Interclub
Motorsport UK Championship Grade:	Grade C

### 1.2 OFFICIALS:

1.2.1 Championship Co-ordinator:	David Wheadon
1.2.2 Championship Eligibility Scrutineer:	Richard Hargreaves
1.2.3 Championship Stewards:	Robert Lentell Brian Hemmings John Leck Jonathan Kimber

Any three Championship Stewards will constitute a quorum. In the event of any of the Championship Stewards listed above being unavailable or being unable to consider any particular matter due to a perceived conflict of interest, the organisers reserve the right to appoint an alternative Championship Steward or, if deemed to be necessary, more than one alternative Championship Steward.

**NCR 4.1.1.2.** The Championship Stewards may only adjudicate on any disputes irregularities or appeals arising from the published Championship regulations. They are also empowered to consider any request from the Championship Co-ordinator to penalise any Competitor for any breach of Championship Regulations and after holding a formal hearing those Stewards may impose a penalty in accordance with NCR Chapter 2 subject to the rights of Appeal to the National Court there.

1.2.4 Championship Clerk of the Course:	N/A
1.2.5 Championship Drivers Representative:	Jim Baynam

### 1.3 COMPETITOR ELIGIBILITY:

#### 1.3.1 Entrants must:

- be fully paid up valid membership card holding members of the BARC and
- be registered for the Championship and
- be in possession of a valid Motorsport UK Entrants Licence.

#### 1.3.2 Drivers and Entrant/Drivers must, at the time of submitting a race entry, be:

- a current Racing member of the BARC
- be registered for the Championship (refer 1.6.7c)
- be in possession of valid Competition Race Club Status Licence, as a minimum or
- Or be in possession of the highest grade of national Race licence or valid FIA International Licence, together with their ASN's written consent (NCR 6.3.1.6 and FIA ISC Article 2.3.7.b applies).
- If participation in the Championship requires absence from education a driver, in full time school education is required to have the approval of their head teacher and a letter stating such approval from their school in order to fulfil registration for the Championship. A driver shall not take time out of their education to participate in motor sport without the prior written approval of their education establishment.
- Agree to abide by the Motorsport UK Race With Respect campaign at all times to promote a safe, enjoyable and fair environment.

1.3.3 All necessary documentation must be presented for checking at all rounds when signing-on. This will include both the competition licence and club membership card.

#### 1.4 REGISTRATION:

1.4.1 All competitors must register for the Championship by returning the Registration Form with the Registration Fee to the MGOC a minimum of 48 hours prior to the date of the meeting being entered.

1.4.2 The Registration Fee is £ £40 and should be made payable to “MG Owners’ Club”.

1.4.3 Competition numbers will be issued by MGOC, these will be the permanent numbers for the Championship season.

#### 1.5 CHAMPIONSHIP EVENTS:

The Championship is scheduled to be contested over 7 events as follows:

ROUNDS	DATE	VENUE	CLUB
1 / 2	21/22 March	Donington Park *GP	BARC
3 / 4	11/12 April	Cadwell Park*	BARC
5/6	16/17 May	Oulton Park International*	BARC
7/8	4/5 July	Thruxton*	BARC
9/10	1/2 August	Brands Hatch*	BARC
11/12	12/13 September	Snetterton 300*	BARC
13/14	3/4 October	Silverstone International*	BARC

\* Subject to issuing of Track Licence

#### 1.6 SCORING:

1.6.1.1 Points will be awarded to Competitors listed as classified finishers in the Final Results as follows:

1st - 12, 2nd - 10, 3rd - 8, 4th - 7, 5th - 6, 6th - 5, 7th - 4, 8th - 3, 9th - 2, all other finishers - 1

1.6.1.2 Should there be three or less starters in a Class, reduced points will be awarded as follows:

1st - 5, 2nd - 3, 3rd - 1

1.6.1.3 Should for whatever reason, the scheduled race duration (as may be amended by Official Bulletin) not be completed, the following points will be awarded:

More than 50% the scheduled duration will attract 100% points.

More than 2 laps and up to 50% of the scheduled duration will attract 50% points.

A race of less than 2 laps will be declared null and void in accordance with Motorsport UK NCRs and no points awarded.

1.6.2 If an event is stopped and restarted the original number of starters in each class will determine the points to be scored.

1.6.3 In each race an additional point will be awarded to the driver in each Class setting the fastest race lap, provided that there is a minimum of two starters in the Class. A further point will be awarded to the driver starting the race from pole position in each Class, provided that there is a minimum of two starters in the Class. This point will not be awarded where the grid for the race is set by the second fastest time in qualifying.

1.6.4 The totals from all qualifying events run less two will determine final Championship points and positions. 1.6.5 Ties shall be resolved using the formula in NCR 4.3.4.

1.6.6 Where the race distance has been reduced in accordance with article 2.6 below, it shall still count as a full point scoring round.

1.6.7 Competitors entering the Invitation class may be permitted on an individual round basis and:

a) will not score points and for the purpose of points scoring will be ignored.

b) will not be allowed to take their place on the podium and qualify for any event awards.

c) must comply with the eligibility criteria as prescribed in article 1.3 above, with the exception of 1.3.1 (b)



ADRIAN FLUX  
Insurance for the individual



## 1.7 AWARDS:

1.7.1 All race awards are to be provided by the MGOC unless otherwise stated.

1.7.2 Per Event:

- MGOC will provide a trophy to the overall winner and each Class winner subject to there being a minimum of two starters in the Class.

1.7.3 Championship:

- A trophy will be awarded to the overall Championship winner and to those finishing 1st, 2nd and 3rd in each Class.

1.7.4 Presentations:

- Awards will be presented at the end of each Event and/or at the end of the Championship at the designated presentation ceremony. Attendance at any such ceremony is mandatory and failure to attend may result in the loss of all awards.

1.7.5 Entertainment Tax Liability:

*Prize money and Bonuses shall be posted to the Entrants within thirty days of the results being declared final after each Event. In accordance with current government legislation, the BARC is legally obliged to withhold tax at the basic rate on all payments to non-UK resident sportsmen/women and account to HMRC using form FEU1, the quarterly return of payments made to non-resident entertainers and sportsmen/women. That is, those persons who do not have a normal permanent residence in the UK and the UK does not include the Isle of Man, Channel Islands or Eire. This means that, as the organiser, the BARC is required to deduct tax at the current rate applicable from any such payments they may make to non-UK residents. Under certain circumstances, it may be possible for competitors to enter into an agreement with the Inland Revenue to limit the tax withheld. Any application for such an arrangement must be made in writing and not later than 30 days before the payment is due.*

For further information contact:

HMRC Personal Tax International, Foreign Entertainers Unit, St John's House, Merton Road, Liverpool L75 1BB, Tel: 01514 726488, Fax: 01514 726483.

1.7.6 Title to all Trophies:

If Provisional Results or Championship Tables are revised after any presentations and these revisions affect the distribution of awards the Competitors concerned must return them to the organisers in good condition within 7 days.

## 2. CHAMPIONSHIP EVENT MEETINGS & RACE PROCEDURES

### 2.1 ENTRIES:

- 2.1.1 Competitors are responsible for sending in correct and complete entries with the correct entry fee prior to the closing date for entries before each Event.
- 2.1.2 Submission date of entries will be deemed as the date of receipt of the BARC Alpha Timing entry system. Incorrect or incomplete entries (including driver to be nominated entries or non-payment of the entry fee) are to be held in abeyance until they are complete and correct and the date of receipt for acceptance of entry purposes must be the date on which the Event Organiser receives the missing or corrected information and/or entry fee.
- 2.1.3 Any withdrawal of Entry or Driver/Vehicle changes made after acceptance of any entry must be notified to the Event Organisers in writing. NCR 3.11.1.1 applies.
- 2.1.4 The Entry Fee for each event shall be specified in the SRs and on the entry form.
- 2.1.5 The maximum number of Vehicle that can start a race is defined by the track licence. Entries will be accepted by the date of receipt by the organising club of a correctly completed entry form and full payment of the appropriate entry fee. In the event of entries exceeding the maximum permitted under the track licence a maximum of six reserves may be nominated. Reserves will be listed in the Final List of Entries published with Final Instructions or in a Bulletin.

### 2.2 BRIEFINGS:

Organisers should notify Competitors of the times and locations for all briefings in the Final Instructions for the meetings. Competitors must attend all briefings.

### 2.3 QUALIFICATION PRACTICE:

- 2.3.1 Should any Qualifying session be disrupted the Clerk of the Course shall not be obliged to resume or re-run the session; the decision of the Clerk of the Course shall be final.
- 2.3.2 Each driver must complete a minimum of 3 laps in the Vehicle to be raced and in the correct session, in order to qualify. Any Vehicle qualifying out of session is subject to NCR 12.6.3.4.
- 2.3.3 The grid for Race 1 will be set by the fastest times set in the official Qualifying session. The grids for Race 2 will be set by the 2<sup>nd</sup> fastest time in Qualifying. In the event of a triple-header, the grid for Race 3 will be set by the 3<sup>rd</sup> fastest times in Qualifying.
- 2.3.4 Any Vehicle listed as a Reserve (refer 2.1.5) will be permitted to take part in the official Practice /Qualification session. Reserves will take the place of any Vehicle that withdraws after the Practice/Qualification and will take a grid position in accordance with the time as set in the Practice/Qualification session.

### 2.4 RACES:

Should any race be disrupted the Clerk of the Course shall not be obliged to resume or re-run the race (NCR 12.6.9) in addition article 1.6.4 above applies.

### 2.5 STARTS:

- 2.5.1 All Vehicles will be released to form up on the grid prior to the start in formation as specified on the grid sheet.
- 2.5.2 The start will be via a Standing start. The countdown procedure and audible warning sequence prior to the start of the race shall be:

SIGNAL	INSTRUCTION
<b>1 Minute</b>	Start engines and clear the grid
<b>30 Seconds</b>	Be prepared for start of the Green Flag Lap
<b>Green Flag</b>	Complete one lap and reform in grid positions
<b>5 Seconds</b>	The grid is complete, prepare for start. The red lights will be switched on five seconds after the 5 second board is withdrawn and will be extinguished between 2 and 7 seconds later
<b>Red Lights Off</b>	Race Start

- 2.5.3 Any Vehicle removed from the grid or driven into the pits on the Green Flag lap shall be held in the pit lane and may start the race after the last Vehicle to take the start from the grid has passed the start-line or pit lane exit, whichever is later.



- 2.5.4 Any driver unable to start the Green Flag or start is required to indicate their situation as per NCR 12.6.6.11. In addition, any driver unable to maintain their grid position on the Green Flag Lap, to the extent that all other Vehicles are ahead of them, may complete the Green Flag lap but must remain at the rear of the last row of the grid but ahead of any Vehicles to be started with a time delay.
- 2.5.5 In the event of any starting lights failure the Starter will revert to use of the National Flag once all competitors have been advised of the fact.
- 2.5.6 The Organisers reserve the right to amend this start procedure via a bulletin issued to all competitors. This may involve changing the method of starting and/or the countdown procedure leading up to the start signal being given.
- 2.5.7 A Vehicle will be deemed to have started the race if it is on the grid at the showing of the one-minute board – refer NCR 12.6.5.9.
- 2.5.8 The organisers reserve the right to amend the start procedure to suit the constraints of the timetable, this may include in exceptional circumstances removal of the Green Flag lap. Competitors will be advised of any such change as soon as practicable but before being released to the grid.

## 2.6 SESSION RED SIGNAL:

- 2.6.1 Should the need arise to stop any race or practice, red signals will be displayed at the Start line and at all Signalling Points around the Circuit.

This is the signal for all drivers to cease circulating at racing speeds, to slow to a safe and reasonable pace and to return to the pit lane, during practice, and to the starting grid area, during a race, unless otherwise directed by Officials. Marshals should revert to displaying yellow flags to indicate to Drivers the particular location of any incident hence supplementing the Light Panels.

- 2.6.2 Vehicles should not enter the Pits unless directed to do so and all Vehicles in the pit lane during a red flag period must take any restart from the pit exit.
- 2.6.3 All Competitors who are able to take part in any restarted race may do so in accordance with NCR 12.6.9.3. The race will restart behind the Safety Car. The starting order shall be based upon the order of crossing the finish line at one lap less than the number of laps completed by the leader at the time of first showing the Red Signal. The Safety Car will lead the Vehicles around the circuit in accordance with the principles set out in the NCR 12.8.2:

Operation of the Safety Car. It will resume the race in accordance with NCR 12.8.2.10 to 12.8.2.12 in the usual way. The length of the restarted race will be determined by the Clerk of the Course, and race time will commence at the start of the Safety Car period.

## 2.7 PITS, PADDOCK & PITLANE SAFETY:

- 2.7.1 Pits & Paddock: Competitors must ensure that the Motorsport UK, Circuit Management and Organising Club Safety Regulations are complied with at all times. In addition, any paddock plan issued by the Organisers must be complied with and the minimum amount of space should be used when setting up.
- 2.7.3 Pit Lane: The outer lane or lanes are to be kept unobstructed to allow safe passage of Vehicles at all times. The onus shall be on all Drivers to take all due care and respect the pit lane speed limits. No-one under the age of 16 is permitted access to the pit lane unless they are the holder of a Motorsport UK Junior Race licence
- 2.7.4 Refuelling: May only be carried out in accordance with the Motorsport NCRs, the Organising Club Regulations, Circuit Management Regulations and the SRs or Final Instructions issued for each Circuit/Event.
- 2.7.5 Speed Limit Pit Lane Speed Limit will be 60 kph.

## 2.8 RACE FINISHES:

After taking the Chequered Flag drivers are required to:

- progressively and safely slow down
- remain behind any competitors ahead of them,
- return to the Pit Lane Entrance/Paddock Entrance as instructed,
- comply with any directions given by Marshals or Officials

- e) keep their helmets on and harnesses done up while on the circuit or in the pit lane
- f) place their car into the Parc Fermé where it must remain until released by the Championship Eligibility Scrutineer or their deputy
- g) Attend any podium presentation that may be required

## **2.9 RESULTS:**

All Practice Timesheets, Grids, Race Results are to be deemed Provisional until all vehicles are released by Scrutineers after Post Practice/Race Scrutineering and/or after completion of any Judicial or Technical Procedures. (NCR 3.6)

## **2.10 TIMING MODULES:**

It is the Competitors responsibility to ensure that a working transponder is fitted to the vehicle in accordance with NCR 12.6.2. No electronic equipment may be placed within five metres of any official timing line and any breach of this may result in the confiscation of the equipment concerned.

## **2.11 QUALIFICATION RACES:**

If any event is oversubscribed the Organising Club may at their discretion run Qualification Races details of which will be published in Final Instructions for the event.

## **2.12 OPERATION OF SAFETY CAR:**

The Safety Car will be brought into operation and run in accordance with General Regulation NCR 12.8.2.

## **2.13 ONBOARD CAMERAS:**

Cameras may be fitted to vehicles provided that the camera footage obtained is not for commercial use. The Clerk of the Course, Stewards and Championship organisers may make use of any such footage in reaching their decisions on any judicial matters. Ch.7 App.9 applies. Please ensure that SD cards are regularly cleared to assist Clerks with identification and review of relevant footage.

### 3. SPECIFIC CHAMPIONSHIP REGULATIONS

- 3.1 The organisers may, at their total discretion; run a qualification race should the entries received exceed 150% of the number of race starters allowed in the track licence for the circuit in question should there be sufficient time in the meeting timetable to allow for this procedure. Should this be the case, the Final Instructions for the Event will carry details of the procedure in question and shall have the same force as these regulations.
- 3.2 The grid for Race1 will be set by the fastest times set in the official Qualifying session. The grids for Race 2 will be set by the 2<sup>nd</sup> fastest time in Qualifying. In the event of a triple-header, the grid for Race 3 will be set by the 3<sup>rd</sup> fastest times in Qualifying
- 3.3 The standard minimum scheduled distance shall be as stated in the Final Instructions. Should any race distance be reduced at the discretion of the Clerk of the Course or Stewards of the Meeting, it shall still count as a points scoring round in accordance with 1.6.1.3.
- 3.4 A driver may enter cars and score points in different Classes at the same Event.
- If a vehicle that has competed in the Race 1 of a double-header meeting is unable to start in Race 2 of that meeting the driver may use another car for Race 2 but will not be eligible to score points in the Class, this is subject at all times to the approval of the Clerk of the Course or their appointed deputy. The driver may use another vehicle, which must comply with the relevant Class Regulations and have a valid scrutineering ticket for the Event in question.
- 3.5 Two drivers may enter the same car at double/triple header meetings. In this situation the driver who sets a time in the official Qualification session will take their appropriate position on the grid for Race 1. that the second driver must qualify out of session and start from the back of the grid in Race 2. Nominated Reserves take precedence over any driver who qualifies out of session (refer NCR12.6.3.4).
- 3.6 The use of tyre heating/heat retention devices, tyre treatments and compounds is prohibited.
- 3.7 The term **OEM** as used in the Regulations is taken to refer to the following definitions as detailed in NCR Chapter 1 Appendix 1.
- STANDARD PART:** Is a part, the specification, features, location and method of operation of a part are as provided when new by the motor manufacturer for the model and date of car as shown on the entry form.
- STANDARD PATTERN PART:** A replacement part that has a similar form shape and features as the standard part and is made using similar materials and manufacturing processes e.g. a standard part, manufactured by a non-original equipment supplier that is fully interchangeable with the standard part.
- 3.8 By registering for the Championship all competitors and their associates commit to positively promote and demonstrate the Motorsport UK's Respect Code which is appended to these regulations (Appendix 1).
- 3.9 Where any reports of disrespectful conduct are judged to be well founded the Championship organisers may issue warnings or require remedial actions and/or report the matter to the Championship Stewards who may impose appropriate penalties which can include loss of Championship points and/or race bans through to Championship Expulsion and referral to Motorsport UK.
- 3.10 It is imperative that we promote the safety and wellbeing of young people and adults at risk. In addition to this all participants must be aware of their behaviour and conduct at all times and abusive language and harmful behaviour will not be tolerated. Any such incidents must be reported to the Championship Coordinator and/or Safeguarding Officer who will also relay the report Motorsport UK. Details of the Motorsport UK Policies and Guidelines are available at [www.motorsportuk.org/resource-centre](http://www.motorsportuk.org/resource-centre) by selecting Policies and Guidelines.

## 4. PENALTIES

All penalties will be in accordance with NCR Chapter 2.

### 4.1 Infringements of Technical Regulations:

#### 4.1.1 Arising from post practice Scrutineering or Judicial Action:

Minimum Penalty: The provisions of NCR 2.8.1.21.

#### 4.1.2 Arising from post-race Scrutineering or Judicial Action:

Minimum Penalty: The provisions NCR 2.8.2.2a/2.8.2.2b.

For infringements deemed to be of a more serious nature the Clerk of the Course may invoke the provisions of NCR 2.8.2.2c. However, if the Clerk of the Course believes that there is some mitigation surrounding the infringement then NCR 2.8.2.5 need not be implemented.

### 4.2 All infringements of non-technical Motorsport UK NCRs and the Sporting Regulations will be dealt with in accordance with these Championship Regulations and the General Regulations of Motorsport UK.

### 4.3 Additional specific Championship penalties:

#### 4.3.1 Any Competitor adjudged to have made a false start or breached any part of the start procedure will be penalised by means of a ten second penalty being added to their total race time.

#### 4.3.2 Competitors breaching the pit lane speed limit will be subject to penalties as provided for in Motorsport UK NCRs, typically being a fine of £10 per kph in excess of the limit during practice or qualifying during a race.

#### 4.3.3 Any Competitor disqualified from the results of an Event for a technical or driving standards offence will not be allowed to count the score (including, if appropriate, the point gained for fastest lap) as part of any dropped scores as detailed in 1.6.4.

#### 4.3.4 Any Competitor may be called before the Championship Stewards who at their discretion may take further action against the Competitor. This may include, but is not limited to, the loss of Championship points, a fine to a maximum of £10,000 or disqualification from part or all of the Championship.

#### 4.3.5 Stop/Go or Drive Through procedures and penalties will not be applied. All incidents or situations will be investigated by the Clerk of the Course on completion of the race.

#### 4.3.6 Any vehicle not carrying the mandatory Championship decals may be placed into the invitation class. This is subject to the required decals being available to competitors on the day of the meeting.

## 5. TECHNICAL REGULATIONS – CLASSIC CLASS

**THE ELIGIBILITY SCRUTINEER RESERVES THE RIGHT TO SEAL AND SUBSEQUENTLY DISMANTLE ANY PART OF A COMPETING CAR. ANY REBUILDING COSTS WILL BE BORNE BY THE COMPETITOR.**

### 5.1 INTRODUCTION:

- 5.1.1 The term **OEM** (Original Equipment Manufacture) as used throughout these Regulations relates to the Motorsport UK definition of “Standard Parts” and “Standard Pattern Parts” and stated in NCR Chapter 1 Appendix 1 as noted in Clause 3.7.
- 5.1.2 No modifications are permitted from the **OEM** specification other than those specified hereafter or listed in official Technical Bulletins as issued by BARC. It must be clearly understood that if the following texts do not clearly state that you can do the works you should work on the principle that you cannot.
- 5.1.3 Where items are listed in the following texts under the headings “Prohibited Modifications”, it must be understood that this is not an exhaustive list and the references made in 5.1.2 must be understood and acknowledged.
- 5.1.4 The term "standard" applies to components shown in the exploded diagrams in the workshop manuals:
- AKD 4957 - MGB / MGB GT
  - AKD 4021 - 1275 Midget
  - AKM 4071/B - 1500 Midget

### 5.2 GENERAL DESCRIPTION:

- 5.2.1 The Classic Class is open to MGB, MGB GT, MG Midget/Sprite 1275 and MG Midget 1500.
- 5.2.2 MOT certificates, Insurance and Road Fund licences are not required.
- 5.2.3 With the exception of those items specifically permitted within these Regulations, no MG Rover or MG dealer offered factory options are permitted without the written approval of the Championship Co-ordinator.

### 5.3 SAFETY REQUIREMENTS:

- 5.3.1 NCR 7.3 Regulations will apply.
- 5.3.2 Six point roll cages are mandatory for all cars.
- 5.3.3 No part of the roll cage is permitted to project through the front bulkhead.
- 5.3.4 Towing eyes in accordance with NCR 12.13.1.3 – 1.4 must be fitted.

### 5.4 CHASSIS:

- 5.4.1 The bodyshell may be seam welded.

### 5.5 BODYWORK AND INTERIOR:

#### Permitted Modifications

- 5.5.1 Rear view mirrors must be fitted to each side of the car
- 5.5.2 All original factory fitted interior trim panels must be retained but interior carpets and passenger seats may be removed.
- 5.5.3 Heaters and ducting may be removed.
- 5.5.4 Bumpers may be removed subject to 5.18.1.  
MGB/MGBGT originally fitted with rubber bumpers may be converted to chrome bumpers.  
Non-**OEM** bumper mountings are permitted.
- 5.5.5 Rubber bumpers and backing plates may be modified or lightened
- 5.5.6 Fibreglass bonnets, front wings and boot lids are permitted on all cars.
- 5.5.7 MGB may fit aluminium bonnets.
- 5.5.8 MGB Roadster and Midget/Sprite may fit a fibreglass boot lid.
- 5.5.9 MGB GT may fit GRP or metal skin tailgates with 4mm polycarbonate rear window.



- 5.5.10 MGB GT may fit 4mm polycarbonate side windows and remove the window winding mechanisms. The door quarter light frames and original glass must be retained.
- 5.5.11 MGB and MGB GT may fit Sebring type headlamp covers.
- 5.5.12 Bonnet, boot and tailgate hinges may be removed.
- 5.5.13 Front and rear Leyland ST pattern spoilers may be fitted to MGB and MGB GT only and must be strictly in accordance with original size and specification.
- 5.5.14 Hardtops are free but fastback types are not permitted.
- 5.5.15 MGB/MGB GT may remove the original battery support framework.
- 5.5.16 The original dashboard carcass must be retained except where as agreed in writing with the Championship coordinator.
- 5.5.17 MG Midget and MGB/MGB GT may flare the rear wheel arches sufficiently to allow tyre clearance.
- 5.5.18 Square wheel arch Midgets may fit round arch rear wings.
- 5.5.19 MGB/MGBGT may fit Sebring type front and rear valances

#### Prohibited Modifications

- 5.5.20 Structural components and body panels must not be removed.
- 5.5.21 Flared wheel arches except as stated in 5.5.-17.
- 5.5.22 Louvered or modified bonnets.
- 5.5.23 One piece GRP front bonnet/wing assemblies.

## **5.6 ENGINE:**

#### Permitted Modifications

- 5.6.1 1275 engines may be fitted into 1500 Midget bodysHELLs however the vehicle must otherwise conform to a 1275 Midget in all other respects.
- 5.6.2 Early Midget/Sprite may use the later 1275cc A series engine.
- 5.6.3 1275 Sprite/Midget may use the A or A Plus type cylinder block.
- 5.6.4 Steel billet crankshafts.
- 5.6.5 The sump may be baffled to prevent surge.
- 5.6.6 The **OEM** steel flywheel must be fitted. This flywheel may be lightened subject to the following minimum weights, including ring gear:
  - 1800cc B series engines: 5.9 kg
  - 1500cc Midget engines: 6.4 kg
  - 1275cc A series engines: 6.4 kg
- 5.6.7 The maximum bore sizes are as follows:
  - 1275 Midget: 2.850
  - 1500 Midget: 2.970
  - MGB/MGB GT: 3.220
- 5.6.8 The maximum crankshaft strokes are as follows:
  - 1275 Midget: 3.209
  - 1500 Midget: 3.452
  - MGB/MGB GT: 3.507
- 5.6.9 The crankshaft journals may be reground to normal tolerances and undersize shells fitted. Steel main caps may be fitted to the crankshaft journals.
- 5.6.10 Non **OEM** bolts, studs and fixings may be used.



- 5.6.11 Camshaft profiles are free subject to 5.6.21.
- 5.6.12 Forged steel conrods are permitted. There is no minimum weight for conrods.
- 5.6.13 OEM conrods may be modified to accept floating gudgeon pins.
- 5.6.14 Forged or cast pistons may be used.
- 5.6.15 Engine blocks and cylinder heads may be skimmed.
- 5.6.16 1275 Midget cylinder head may be gas flowed.
- 5.6.17 MGB/MGB GT may use 12H2709 or 12H4736 cylinder head castings. The 12H4736 casting may use the 1.625" inlet valve but any grinding of the inlet port is restricted to a maximum of 20mm below the bottom of the valve seat. No further machining is permitted.
- 5.6.18 For MGB the valve throat diameters must not exceed:
- Inlet: 1.530"
  - Exhaust: 1.230"
- 5.6.19 Valve seats may be restored by re-cutting or fitting inserts, three angle valve seats are permitted but no additional reworking or machining is allowed.
- 5.6.20 The cross sectional dimensions of the valves in all planes must remain as **OEM**.
- 5.6.21 The valve head diameters must not exceed:
- 1275 Midget: Inlet 1.312" / Exhaust 1.156"
  - MGB/MGBGT: Inlet 1.630" / Exhaust 1.345"
  - 1500 Midget: Inlet 1.380" / Exhaust 1.175"
- 5.6.22 Maximum valve lift is as follows:
- A Series engines: 0.333"
  - B Series engines: 0.390"
  - 1500 engines: 0.380"
- All taken with zero tappet clearance there is NO further tolerance allowed above these figures.
- 5.6.23 Valve springs and valve guide material are free.
- 5.6.24 Vernier timing sprockets.
- 5.6.25 Single or double row timing chains
- Prohibited Modifications
- 5.6.26 – Any machining to the webs of OEM crankshafts other than to achieve correct dynamic balance
- 5.6.27 With the specific exception of 5.6.17 MGB and 1500 Midget cylinder heads must not be modified, reworked or polished. Casting marks must remain as the manufacturer intended.
- 5.6.28 Offset valve rockers or bushes.
- 5.6.29 WAISTED STEM VALVES.**
- 5.7 COOLING:**
- 5.7.1 Oil coolers may be fitted within the periphery of the bodywork.
- 5.7.2 The original heater matrix may be replaced with an aftermarket cooler for additional cylinder head cooling.
- 5.7.3 The heater may be removed.
- 5.7.4 Electric cooling fans may be fitted.
- 5.7.5 Non **OEM** radiators are permitted, these must fit on the original mounting points.



## 5.8 CARBURETTORS AND INDUCTION SYSTEM:

5.8.1 The following **OEM** carburettors are permitted:

- MGB/MGB GT: 2 x 1½" HS4 or HIF4
- 1500 Midget: 2 x 1½" HIF4
- 1275 Midget: 2 x 1 ¼" HS2

5.8.2 No internal re-shaping or polishing is permitted.

5.8.3 Carburettor jets, needles and damper springs are free.

5.8.4 Inlet manifolds must remain as **OEM** with no additional internal machining or polishing.

5.8.5 Air filters are free.

5.8.6 Airboxes and carburettor ducting are permitted.

## 5.9 EXHAUST SYSTEM:

5.9.1 Exhaust manifolds are free on all cars.

5.9.2 Exhaust systems are free beyond the manifold but must exit at the rear of the car.

## 5.10 IGNITION SYSTEM:

5.10.1 Engine management systems of any type are not permitted, only mechanical advance and retard is allowed.

5.10.2 The original distributor must remain in use in its original location.

5.10.3 External programme sensitive or adjustable advance and retard is not allowed.

5.10.4 Single pulse non-programmable electronic ignition systems (eg. Aldon Ignitor, Lucas, or Lumenition) are allowed.

5.10.5 Non-standard fuel pumps and pressure regulators are permitted.

## 5.11 SUSPENSION:

### Permitted Modifications

5.11.1 Spring rates are free but they must be of the original type and materials. The top leaf of a rear leaf spring may be inverted.

5.11.2 Lowering blocks may be fitted to the rear springs.

5.11.3 Wheel camber angles are free. Non-**OEM** trunnions, bushes or wishbone arms are permitted in order to achieve this.

5.11.4 Anti-roll bar mounting blocks and all suspension bushes and leaf spring pads may be of non **OEM** material.

5.11.5 Rear anti-roll bars may only be fitted to cars where they were originally fitted to the car in question.

5.11.6 MGB and MGBGT may fit up to 20mm anti-roll bars.

5.11.7 All Midgets/Sprites may fit up to 17.5mm anti-roll bar.

5.11.8 Lever arm dampers must be retained, they may be fitted with adjustable valves.

5.11.9 Front and rear suspension bump stops may be shortened.

### Prohibited Modifications

5.11.10 Component dimensions and pick-up points must remain as **OEM** except as stated in 5.11.3.

5.11.11 Parabolic or single leaf rear springs.

5.11.12 Spherical bearings (eg. rose joints)

## 5.12 TRANSMISSION AND FINAL DRIVE:

### Permitted Modifications

5.12.1 The gearbox and ratios must be as **OEM** to a UK supplied production model of the car in question.

5.12.2 MGB/GT originally fitted with a 3 synchro gearbox may change for the later 4 synchro gearbox.

5.12.3 Overdrive is permitted on MGB/MGBGT only.



- 5.12.4 MG Midgets/Sprites may fit competitions type splined half shafts with separate end flange.
- 5.12.5 Banjo axles may be fitted to any model year of MGB/MGBGT. Banjo axle casings that have been modified to accept the later Salisbury axle hubs, half shafts and brake drums are permitted.
- 5.12.6 Clutch plate material is free but the clutch must be of single plate design and must mount to the bolt and dowel holes of an original **OEM** flywheel.
- 5.12.7 1275 Midget may use the gearbox casing and ratios as fitted to 1500 Midget using a suitable steel adaptor plate.
- 5.12.8 The following differential ratios are permitted:
  - MGB/MGB GT: 3.9, 4.1, 4.3
  - Midgets/Sprites: 3.7, 3.9, 4.2

#### Prohibited Modifications

- 5.12.9 Non-**OEM** gearboxes or close ratio gears.
- 5.12.10 Any form of locked, limited slip or torque sensing differentials.
- 5.12.11 Any form of traction control or launch control device.

### **5.13 ELECTRICAL SYSTEMS:**

- 5.13.1 Exterior lighting must remain fully operational.
- 5.13.2 Cars originally fitted with a dynamo may be changed to an alternator.
- 5.13.3 The dynamo/alternator must remain fully operational at all times. Pulley diameters are unrestricted.
- 5.13.4 MGB/MGBGT may fit a single 12 volt battery, the battery location is free.
- 5.13.5 Gel type racing batteries are permitted.
- 5.13.6 Non **OEM** starter motors are permitted.
- 5.13.7 Data logging systems are permitted.

### **5.14 BRAKES:**

#### Permitted Modifications

- 5.14.1 Front disc backing plates may be removed.
- 5.14.2 Rear wheel cylinders may be changed for larger or smaller diameter.
- 5.14.3 All cars may fit dual circuit brake systems using **OEM** components as fitted to later cars.
- 5.14.4 Rear brake drums and backing plate may be drilled to assist ventilation. Two holes may be drilled in the back plate, these must not exceed 35mm diameter.
- 5.14.5 Uprated brake pads, linings and hoses may be fitted.
- 5.14.6 Brake ducting is allowed providing no modifications are made to the bodywork.

#### Prohibited Modifications

- 5.14.7 Vented, slotted, dimpled, composite, modified discs-

### **5.15 FUEL SYSTEM:**

- 5.15.1 The fuel tank must remain in its original position.
- 5.15.2 The **OEM** fuel tank or an equivalent aftermarket alternative must be used. It may be foam filled.
- 5.15.3 Permitted Fuels as defined in NCR 8.1.1.7a must be used. An additive is permitted for lead replacement only to reduce valve seat recession - refer NCR 8.1.1.7a.ii.
- 5.15.4 Non-**OEM** fuel pumps and pressure regulators are permitted.



## 5.16 WHEELS/STEERING:

### Permitted Modifications

- 5.16.1 Wheels may be either the manufacturer's original steel type or a non standard pattern which fit on the original hubs without modification.
- 5.16.2 MG Midget may fit up to 6mm spacers to the rear hubs. Longer wheel studs are permitted.
- 5.16.3 Maximum wheel sizes are as follows:
- MGB/MGBGT: 5.5" wide x 14" diameter
  - MG Midget/Sprite: 5" wide x 13" diameter

### Prohibited Modifications

- 5.16.4 Non-standard steering racks and associated components.
- 5.16.5 Spherical bearings (eg. rose joints).

## 5.17 TYRES:

- 5.17.1 Cars are required to use the following tyres:
- MGB/GT: 185/60R14 Toyo 888R (GG Medium compound only)
  - Midget/Sprite: 185/60R13 Toyo 888R (GG Medium compound only)
- 5.17.2 The compound marking on the sidewall is to remain clearly visible at all times. Any tyre not clearly showing the manufacturer's original compound marking will be deemed non-compliant.
- 5.17.3 The nominated tyre supplier is: Adams and Page, Lincoln Road, Cressex Estate, High Wycombe, Bucks, HP12 3RO. Tel: 01494 445389

## 5.18 WEIGHTS:

- 5.18.1 The minimum weights as the car finishes qualifying or race with the driver on board are as follows:
- MGB/MGB GT: 965kg
  - 1275 Midget: 780kg
  - 1500 Midget: 780kg
- 5.18.2 Ballast is permitted, this must be securely fixed in the front passenger footwell.
- 5.18.3 The Championship Organisers reserve the right to review and alter weight limits up to a maximum of two occasions per year with a minimum of 14 days' notice to the Motorsport UK and competitors concerned.

## 5.19 NUMBERS AND CHAMPIONSHIP DECALS:

- 5.19.1 Race numbers are to be fitted to 430mm wide x 300mm high white number backgrounds on each door and the bonnet or yellow numbers may be fitted to the doors and windscreen as stated in NCR 12.4.5.
- 5.19.2 An Adrian Flux sunstrip is to be affixed to the top of the front windscreen.
- 5.19.3 Adrian Flux decals are to be fitted on each side of the car, the location is free.
- 5.19.4 MGOC/BARC decals are to be positioned on each side of the car but the position is free.
- 5.19.5 MGOC reserves the right to request that additional decals are fitted at any time.
- 5.19.6 All decals are provided on request by the MGOC to registered competitors. Any car not displaying the required decals may be subject to the penalties as defined in 4.3.6.

## 6. TECHNICAL REGULATIONS – CLASS B

**THE ELIGIBILITY SCRUTINEER RESERVES THE RIGHT TO SEAL AND SUBSEQUENTLY DISMANTLE ANY PART OF A COMPETING CAR. ANY REBUILDING COSTS WILL BE BORNE BY THE COMPETITOR.**

### 6.1 INTRODUCTION:

- 6.1.1 The following Technical Regulations are set out in accordance with the Motorsport UK specified format.
- 6.1.2 The term **OEM** (Original Equipment Manufacturer) as used hereafter relates to “Standard Parts” and “Standard Pattern Parts” as defined in Clause 3.7.
- 6.1.3 No modifications are permitted from the original **OEM** specification other than those specified hereafter or listed in official Technical Bulletins as issued by BARC. It must be clearly understood that if the following texts do not clearly state that you can do the works you should work on the principle that you cannot.
- 6.1.4 Where items are listed in the following texts under the headings “Prohibited Modifications”, it must be understood that this is not an exhaustive list and the references made in 6.1.3 must be understood and acknowledged.

### 6.2 GENERAL DESCRIPTION:

- 6.2.1 Class B of the Championship is open to Maestro 1600, MG Maestro Efi, MG Montego Efi, MG Montego Efi Estate, and ZR160.
- Section 6(3) applies to all cars.
  - Sections 6(4) to 6(20) apply to permitted MG Maestro and Montego models.
  - Sections 6(21) to 6(38) apply to MG ZR160 models.
- 6.2.2 With the exception of those items specifically permitted within these Regulations, no MG Rover or MG dealer offered factory options are permitted without the written approval of the Championship Co-ordinator.
- 6.2.3 MOT Certificates, insurance or Road Fund licenses are not required.

### 6.3 SAFETY REQUIREMENTS:

- 6.3.1 NCR 7.3 Regulations will apply.
- 6.3.2 Six point roll cages are mandatory for all cars.
- 6.3.3 Towing eyes in accordance with NCR 12.13.1.3 – 1.4 must be fitted.

### MG MAESTRO/MONTEGO

### 6.4 CHASSIS:

- 6.4.1 The body shell may be seam welded.
- 6.4.2 Strut braces may be fitted across the front suspension mounts

### 6.5 BODYWORK:

#### Permitted Modifications

- 6.5.1 Plastic inner wheel arches may be removed.
- 6.5.2 The driver’s seat may be changed.
- 6.5.3 The front passenger seat may be removed.
- 6.5.4 All interior trim with the exception of the original dashboard, may be removed.
- 6.5.5 Rear wiper and central locking motors may be removed.
- 6.5.6 Side rubbing strips and front spoiler trims may be removed.
- 6.5.7 Bonnet hinges may be removed.
- 6.5.8 The rear tailgate and bonnet may be lightened or replaced with fibreglass.
- 6.5.9 Heater may be removed.
- 6.5.10 The glass in the front and rear side windows and tailgate may be replaced with polycarbonate.



6.5.11 Manual or electric window winding mechanisms may be removed from all doors. The driver's door must include a sliding access panel.

6.5.12 Two door mirrors must be fitted.

Prohibited Modifications

6.5.13 Structural components must not be removed, lightened or deformed.

**6.6 ENGINE:**

Permitted Modifications

6.6.1 All parts must remain entirely standard as per the makers original specifications unless stated otherwise.

6.6.2 Non-OEM bolts, studs and fixings may be used.

6.6.3 Chemical processes such as Tuftriding or Nitriding.

6.6.4 Steel conrods are permitted.

6.6.5 The OEM steel flywheel must be fitted but there is no minimum weight.

6.6.6 Piston design and material is unrestricted.

6.6.7 The maximum bore sizes are as follows:

- 1600 MG Maestro: 78.00mm
- EFi Maestro: 86.22mm
- EFi Montego: 86.22mm

6.6.8 The maximum crankshaft strokes are as follows:

- 1600 MG Maestro: 87.58mm
- EFi Maestro: 89.00mm
- EFi Montego: 89.00mm

6.6.9 Crankshaft journals may be reground to normal tolerances and undersized shells fitted.

6.6.10 EFi Maestro/Montego valve sizes and design are unrestricted.

6.6.11 Valve seat inserts to enable unleaded petrol to be used.

6.6.12 Cylinder heads may be polished and ported.

6.6.13 Valve guide material is unrestricted.

6.6.14 Valve seats may be cut to a three angle profile.

6.6.15 Cylinder head and engine block faces may be skimmed.

6.6.16 Valve springs are free.

6.6.17 Vernier timing sprockets may be fitted.

6.6.18 The sump may be baffled to prevent surge.

6.6.19 Camshafts profiles are unrestricted but valve lift must not exceed:

- 1600 MG Maestro: 0.350"
- EFi Maestro/Montego: 0.380"

6.6.20 All EFi engines are to have a 10mm hole drilled in the cam cover directly above an inlet cam lobe to allow for valve lift checks to be made.

Prohibited Modifications

6.6.21 Conrods and crankshafts must not be polished.

6.6.22 Modifications to the valve spring collars or valve springs pockets.

**6.7 COOLING SYSTEM:**

6.7.1 Oil coolers may be fitted with the periphery of the bodywork.



6.7.2 1600 Maestro may run EFi Maestro radiators, on all other cars the radiators must remain as originally fitted to that model. Additional supplementary cooling systems are not allowed.

## 6.8 INDUCTION SYSTEM:

6.8.1 1600 MG Maestro must use standard equipment carburettors, no internal re-shaping or polishing is permitted.

6.8.2 1600 MG Maestro carburettor jets, needles and damper springs are free.

6.8.3 1600 MG Maestro maximum choke size is 34mm.

6.8.4 1600 MG Maestro inlet manifolds must remain standard and no additional machining or polishing is permitted. No material may be added.

6.8.5 1600 MG Maestro air filters are free.

6.8.6 On EFi Maestro/Montego non-OEM air filters and airboxes may be fitted.

6.8.7 On EFi Maestro/Montego either MEMS or LUCAS injection systems as fitted by Rover Group may be used but it must be used completely in either form. No cross matching of parts between systems is permitted.

6.8.8 Inlet ducting is allowed on all cars.

## 6.9 EXHAUST SYSTEM:

6.9.1 Non-OEM exhaust manifolds are permitted.

6.9.2 Exhaust systems are free but must exit at the rear of the vehicle.

## 6.10 IGNITION SYSTEM:

6.10.1 On 1600 MG Maestro cars the ignition system is free but programmable ignition systems are not permitted.

6.10.2 Efi Maestro must use either the OEM Lucas ECU or a DTA 2T ECU and the appropriate wiring loom, no additional sensors or inputs are permitted over those originally fitted as OEM by MG Rover

## 6.11 SUSPENSION:

### Permitted Modifications

6.11.1 On all cars the spring rates, wheel camber and suspension geometry are free.

6.11.2 All cars may fit adjustable rate/adjustable platform shock absorbers.

6.11.3 EFi Maestro/Montego may fit anti-roll bars to front and rear. These must be to the original diameter.

6.11.4 1600 Maestro may fit anti-roll bar to the front only. This must be of the original diameter.

6.11.5 All anti-roll bar and other suspension bushes may be on non-standard material.

6.11.6 All cars may fit an anti-drop bush to the Macpherson strut top mounting.

6.11.7 Ride height is free subject NCR 7.2.22.12

### Prohibited Modifications

6.11.8 Wheelbase and track dimensions must remain as **OEM**.

6.11.9 Wheel spacers.

## 6.12 TRANSMISSION:

### Permitted Modifications

6.12.1 Clutch plate material is free but the clutch must be of single plate design and must mount to the bolt and dowel holes of an original **OEM** flywheel.

6.12.2 The clutch drive plate must be of the same diameter as the original equipment.

6.12.3 Gear ratios are free provided they fit within the original casing and allow five forward gears.

6.12.4 Differential ratios on 1600 MG Maestro are free.

### Prohibited Modifications

6.12.5 Locked, limited slip or torque biased differentials.

6.12.6 Traction control or starting control devices.



## **6.13 ELECTRICAL SYSTEMS:**

- 6.13.1 Exterior lighting must remain standard and fully operational.
- 6.13.2 Lightweight non-OEM starter motors and alternators are permitted. Pulley diameters are unrestricted.
- 6.13.3 Data logging systems are permitted.
- 6.13.4 Gel type batteries are permitted.

## **6.14 BRAKES:**

### Permitted Modifications

- 6.14.1 Front disc backing plates may be removed.
- 6.14.2 Competition pads, linings and brake hoses are permitted.
- 6.14.3 Ducting to the front brakes are allowed providing no modifications are made to the bodywork.
- 6.14.4 1600 MG Maestro may use standard size ventilated discs and callipers as fitted to Efi Maestro/Montego.

### Prohibited Modifications

- 6.14.5 Composite, modified discs or drums.

## **6.15 WHEELS/STEERING:**

### Permitted Modifications

- 6.15.1 All cars may use 14" wheels: NAM3300, NAM7222 or NAM9000 or any 15" wheel fitted as standard to MG Maestro or Montego.

### Prohibited Modifications

- 6.15.2 Non-standard steering racks and associated components.

## **6.16 TYRES:**

- 6.16.1 Cars are required to use Toyo 888R (GG Medium compound only)
- 6.16.2 The compound marking on the sidewall is to remain clearly visible at all times. Any tyre not clearly showing the manufacturer's original compound marking will be deemed non-compliant.
- 6.16.3 The nominated tyre supplier is: Adams and Page, Lincoln Road, Cressex Estate, High Wycombe, Bucks, HP12 3RO. Tel: 01494 445389

## **6.17 WEIGHTS:**

- 6.17.1 The minimum weights as the car finishes qualifying or race with the driver on board are:
  - Maestro 1600: 972kg
  - Maestro/Montego Efi: 1030kg
- 6.17.2 Ballast is permitted, this must be securely fixed in the front passenger footwell.
- 6.17.3 The Championship Organisers reserve the right to review and alter weight limits up to a maximum of two occasions per year with a minimum of 14 days' notice to Motorsport UK and competitors concerned.

## **6.18 FUEL TANK/FUEL SYSTEM:**

- 6.18.1. The original fuel tank may be replaced with a foam filled aluminium fuel tank. This must be located in the recess originally intended for the spare wheel. There is no restriction on the tank capacity but it must not protrude above the boot floor. The spare wheel recess above the fuel tank is to be covered with a fixed aluminium sheet which, except for the filler neck, must cover the tank and entire spare wheel recess.

The tank must conform with NCR 7.4.1

- 6.18.2 Permitted Fuels as defined in NCR 8.1.1.7 must be used.
- 6.18.3 Adjustable fuel pressure regulators may be fitted

## **6.19 SILENCING:**

- 6.19.1 A silencer must be fitted as part of the exhaust system to comply with Motorsport UK noise regulations. It must exit at the rear of the car.



ADRIAN FLUX  
Insurance for the enthusiast



## 6.20 NUMBERS AND CHAMPIONSHIP DECALS:

- 6.20.1 Race numbers are to be fitted to 430mm wide x 300mm high white number backgrounds on each door and the bonnet or yellow numbers may be fitted to the doors and windscreen as stated in NCR 12.4.5.
- 6.20.2 An Adrian Flux sunstrip is to be affixed to the top of the front windscreen.
- 6.20.3 Adrian Flux decals are to be positioned on each side of the car, the location is free.
- 6.20.4 The 520mm x 110mm space on the front and rear splitters are to be reserved for a championship sponsors decals.
- 6.20.5 MGOC/BARC decals are to be positioned on each side of the car; location is free.
- 6.20.6 MGOC reserves the right to request that additional decals are fitted at any time.
- 6.20.7 All decals are provided on request by the MGOC to registered competitors. Any car not displaying the required decals may be subject to appropriate penalties as defined in 4.3.6.

## ZR160 CARS

### 6.21 INTRODUCTION:

- 6.21.1 The following Technical Regulations for MG ZR160 cars are set out in accordance with the Motorsport UK specified format and it should be clearly understood that if the following texts do not clearly state that you can do the works you should work on the principle that you cannot.
- 6.21.2 The term **OEM** (Original Equipment Manufacture) as used hereafter relates to “Standard Parts” and “Standard Pattern Parts” as defined in Clause 3.7.
- 6.21.3 No modifications are permitted from the **OEM** specification other than those specified hereafter or listed in official Technical Bulletins as issued by BARC. It must be clearly understood that if the following texts do not clearly state that you can do the works you should work on the principle that you cannot.
- 6.21.4 Where items are listed in the following texts under the headings “Prohibited Modifications”, it must be understood that this is not an exhaustive list and the references made in 6.21.3 must be understood and acknowledged.
- 6.21.5 For technical preference the following MG Rover documents apply:
  - System Description Manual – RCL 0380
  - Service Procedure Manual – RCL 0380
  - PGI Gearbox Manual – RCL 0124
  - K Series Overhaul Manual – RCL 0057

### 6.22 GENERAL DESCRIPTION:

Class B is open to MG ZR160 cars that comply with the specific regulations listed below.

- 6.22.1 MOT certificates, Insurance and Road Fund licences are not required.
- 6.22.2 With the exception of those items specifically permitted within these Regulations, no MG Rover or MG dealer offered factory options are permitted without the written approval of the Championship co-ordinator.
- 6.22.3 Left hand drive cars are not permitted.

### 6.23 BODYSHELL:

- 6.23.1 Bodysells from ZR105 and ZR120 may be used but must conform totally to ZR160 specification.
- 6.23.2 Non-OEM or aftermarket accessories or cosmetic modifications which will not influence the cars overall performance will be allowed subject to the written approval of the Championship co-ordinator.
- 6.23.3 The bodysell may be seam welded.
- 6.23.4 No modifications are permitted to the top suspension turrets.

### 6.24 INTERIOR:

- 6.24.1 All interior trim, dashboard and standard fittings must remain in place and the dashboard is to remain unmodified. Additional switches, gauges and pull cables may be fitted.



- 6.24.2 The driver seat may be changed and the standard seat fixings/runners removed or modified.
- 6.24.3 The passenger seat, rear seat and carpets may be removed.
- 6.24.4 The use of non-standard door trim panels is permitted.
- 6.24.5 The steering wheel may be changed.
- 6.24.6 The rear quarter trim panels and roof lining may be removed.
- 6.24.7 The steering column lock and central locking mechanisms must be disabled.
- 6.24.8 Airbags may be removed or disabled.
- 6.24.9 Air-conditioning systems may be removed.
- 6.24.10 Both front window winder motors must remain fitted and operational.
- 6.24.11 Sound deadening may be removed.
- 6.24.12 The **OEM** heater must be fitted and be fully operational using the **OEM** ducting and vents.

## 6.25 ENGINE:

### Permitted Modifications

- 6.25.1 Two 1.5mm holes are to be drilled in adjacent cam cover bolts for the purpose of fitting engine seals.
- 6.25.2 The maximum bore and stroke dimensions are to be 80.00mm and 89.30mm respectively.
- 6.25.3 The use of Chinese manufactured replacement K series cylinder blocks is permitted. These may be machined only where necessary to allow the fitment of the **OEM** K series crankshaft position sensor.
- 6.25.4 The crankshaft must be the **OEM** part as fitted by MG Rover to the production VVC160 K series engine.
- 6.25.5 Connecting rods must be the **OEM** type or maXpeeding CR-RK-133.  
**OEM** conrods may be bushed or reamed to accept a fully floating gudgeon pin.
- 6.25.6 Aftermarket pistons and liners are permitted but must be to the exact specification, profile and material of the **OEM** MG Rover components as fitted to VVC or 1.8 K series engines.  
Pistons may be machined only to accept the circlips of a fully floating gudgeon pin.
- 6.25.7 The overall height of the cylinder block including the ladder rail must be not less than 281.50mm.
- 6.25.8 The distance from the top of the liner to the shoulder of the liner must be not less than 50mm.
- 6.25.9 The **OEM** steel flywheel must be used. The minimum weight with ring gear is 6.0kg.
- 6.25.10 Cylinder heads may be skimmed but the depth reference datum in the head casting must remain visible.
- 6.25.11 Exhaust valves must conform to **OEM** specification in their entirety, with a maximum head diameter of 27.5mm, a minimum stem diameter of 6mm and a single 45 degree face. It is permitted to have a carbon break in the valve stem to a minimum diameter of 5.5mm.
- 6.25.12 Inlet valves must conform to **OEM** specification in their entirety, with a maximum head diameter of 31.5mm and a minimum stem diameter of 6mm along its entire length. They must have a 45 degree face with a maximum of one single 30 degree back cut.
- 6.25.13 Valve seats may be cut to a maximum of three angles and must conform in their entirety to the dimensions and specifications laid out within the MG Rover K Series Overhaul Manual (RCL 0057) The valve seats must not be blended into the combustion chambers or port walls.
- 6.25.14 Valve springs and hydraulic lifters must be to **OEM** specification
- 6.25.15 Aftermarket valve spring top caps are permitted.
- 6.25.16 Inlet and exhaust cam profiles must remain exactly as the **OEM** MG Rover items.
- 6.25.17 Cam timing must remain as **OEM**.
- 6.25.18 The **OEM** Steel Elastomer or later multi-shim head gaskets are permitted. The early or later type oil rail may be used.
- 6.25.19 The fuel tank breather system must remain as **OEM**. The charcoal canister/purge valve must be fitted.

## Prohibited Modifications

- 6.25.20 Forged pistons.
- 6.25.21 Aftermarket or non-OEM MG Rover camshafts.
- 6.25.22 Any machining to the cylinder head combustion chambers or inlet/exhaust ports.
- 6.25.23 The engine block, oil rail, crankshaft, conrods, pistons and liners must be to OEM specifications and dimensions. They may not be machined, have any material added or removed, or be modified in any way except as detailed in 6.25.4, 6.25.6 and 6.25.7.
- 6.25.24 Any machining to the crankshaft or crankshaft sprocket.
- 6.25.25 Any means of modifying the cam timing eg. vernier timing pulleys, offset or modified camshaft dowels.

### **6.26 COOLING SYSTEM:**

- 6.26.1 The OEM radiator or an identical aftermarket version must be fitted.
- 6.26.2 No additional or uprated oil coolers are permitted.
- 6.26.3 It is permitted to fit a Pressure Relief Remote Thermostat (PRRT) and associated hoses.

### **6.27 INDUCTION SYSTEM:**

- 6.27.1 The induction system as fitted as OEM by MG Rover to ZR160 must be retained in its entirety. No additional ducting is permitted.
- 6.27.2 The paper air filter element may be changed to a foam element. The OEM housing and ducting is to remain in its entirety.
- 6.27.3 The OEM MG Rover 52mm throttle body must be used.

### **6.28 EXHAUST SYSTEM:**

- 6.28.1 The OEM exhaust downpipe and manifold must be fitted. The later six bolt type as fitted to 160 cars may be fitted to earlier cars.
- 6.28.2 An operational catalytic converter must be fitted; this is to be a minimum 100 cell design and must be fitted in the straight section of the exhaust running along the centre line of the car.
- 6.28.3 The exhaust system beyond the catalytic convertor is free but the system must exit at the rear of the car.
- 6.28.4 The welding nodules on the inner face of the exhaust manifold may be removed but the internal bore must not exceed 36mm at any point.
- 6.28.5 The welding nodules on the inner face of the manifold downpipe may be removed but the internal bore must not exceed 41.5mm at any point.

### **6.29 IGNITION SYSTEM:**

- 6.29.1 The original MG Rover MEMS3 ECU must be retained but the mapping within it must be modified by Kmaps.co.uk to MGOC Championship specification MGOC/MEMS3B. ECU's modified by any other suppliers or to any other standard are not permitted.
- 6.29.2 The ECU on any selected MEMS3 equipped car may be sealed and either examined at the circuit or removed from the car and sent to Kmaps.co.uk who will ascertain if the map within the ECU complies with specification MGOC/MEMS3B.
- 6.29.3 MG Owners' Club will hold an ECU modified by Kmaps.co.uk to Championship specification MGOC/MEMS3B. At selected race meetings, the appointed Motorsport UK Eligibility scrutineer may request that the ECU fitted to a car is replaced with the MG Owners' Club ECU. The Motorsport UK Eligibility scrutineer is at liberty to decide which car is subjected to this procedure or to hold a ballot of all cars competing in Class B. In the event that any driver refuses to fit the MGOC ECU, the Motorsport UK Scrutineer will deem the car ineligible to take part in Class B and the car will be placed in the Invitation class until such time as the MGOC ECU is fitted to their satisfaction.

### **6.30 SUSPENSION:**

#### Permitted Modifications

- 6.30.1 The OEM dampers must be retained, these may be re-valved.



6.30.2 Non-**OEM** bushes may only be fitted to the front track control arm (bottom wishbone), front tie bar mounts, front anti-roll bar mounts, front anti-roll bar drop links and rear H frame bushes.

6.30.3 Spring rates are free.

6.30.4 Ride height is free subject to NCR 7.2.22.12

6.30.5 Wheel camber must remain as **OEM**.

Prohibited Modifications

6.30.6 Spherical bearings eg. rose joints.

6.30.7 Strut braces across the front and rear suspension mounts.

6.30.8 Adjustable suspension top mounts or any alterations to the suspension turrets.

6.30.9 Adjustable rate/adjustable platform dampers.

**6.31 TRANSMISSION:**

Permitted Modifications

6.31.1 The clutch plate material is free but the clutch must be of single plate design and must mount to the bolt and dowel holes of an original **OEM** flywheel.

6.31.2 The only gearbox permitted is MG Rover type G4. The gearbox ratios are to be:

- 1st : 3.250 / 2nd : 1.894 / 3rd : 1.307 / 4th : 1.033 / 5th : 0.848

6.31.3 The final drive ratio is to be 4.2:1.

6.31.4 The gear linkage attachment to the gearbox is free and may be wire locked to prevent dislocation of the ball joint.

Prohibited Modifications

6.31.5 Any form of locked, limited slip or torque sensing differentials.

6.31.6 Any form of traction control or launch control device.

6.31.7 Non-**OEM** bushes

**6.32 ELECTRICAL SYSTEM:**

6.32.1 It is permitted to fit a link across the fuel pressure inertia switch.

6.32.2 Data logging systems are permitted.

6.32.3 The **OEM** headlamps must be retained and be fully operational. Plastic film or covers may be fitted to headlamps.

6.32.4 Gel type batteries are permitted but must be fitted in the original location.

6.32.5 All sensors and factory fitted wiring must remain intact. No alterations are permitted unless approved in writing by the appointed Eligibility Scrutineer.

6.32.6 The alternator charging system must remain fully operational at all times.

6.32.7 The rear window wiper and motor may be removed.

**6.33 BRAKES:**

6.33.1 The **OEM** front fog lights may be removed and replaced with ducting but the original aperture dimensions must not be increased.

6.33.2 Up-rated brake pads, linings and brake hoses may be fitted.

6.33.3 The brake discs are to be 283mm at the front and 260mm at the rear.

6.33.4 The ABS system may be disabled or removed.

6.33.5 A pressure limiting valve may be fitted to the hydraulic line to the rear brakes, this must comply with NCR 12.13.5.4-5.5.

**6.34 FUEL TANK/FUEL SYSTEM:**

6.34.1 Permitted Fuels as defined in NCR 8.1.1.7 must be used.

6.34.2 The **OEM** MG Rover fuel tank must be fitted. It may be baffled or foam filled.



ADRIAN FLUX  
Insurance for the enthusiast



6.34.3 The **OEM** MG Rover fuel pressure system and injectors must be retained with no changes or modifications.

6.34.4 The fuel pressure is to be minimum 2.8 bar, maximum 3.2 bar.

### **6.35 WHEELS/STEERING:**

6.35.1 Wheel camber and castor is free.

6.35.2 Only the 16" inch wheels supplied by MG Rover and fitted as **OEM** to MGZR160 saloons are permitted

6.35.3 Wheel spacers up to a maximum of 5mm thick may be fitted to the front wheels only. Longer wheel studs are permitted.

### **6.36 TYRES:**

6.36.1 Cars are required to use the following tyres:

- 195/50R16 Toyo 888R (GG medium compound only).

6.36.2 The compound marking on the sidewall is to remain clearly visible at all times. Any tyre not clearly displaying the manufacturer's original compound marking will be deemed non-compliant.

6.36.3 The nominated tyre supplier is: Adams and Page, Lincoln Road, Cressex Estate, High Wycombe, Bucks, HP12 3RO. Tel: 01494 445389

### **6.37 WEIGHTS:**

6.37.1 The minimum weight as the car finishes qualifying or race with the driver on board is 1050kg.

6.37.2 Ballast is permitted, this must be securely fixed in the front passenger footwell.

6.37.3 The Championship Organisers reserve the right to review and alter weight limits up to a maximum of two occasions per year with a minimum of 14 days notice to the Motorsport UK and competitors concerned.

### **6.38 NUMBERS AND CHAMPIONSHIP DECALS:**

6.38.1 Race numbers are to be fitted to 430mm wide x 300mm high white number backgrounds on each door and the bonnet or yellow numbers may be fitted on the rear doors/hardtop as stated in NCR 12.4.5

6.38.2 An Adrian Flux sunstrip is to be affixed to the top of the front windscreen.

6.38.3 Adrian Flux decals are to be fitted to each side of the car, the location is free

6.38.4 The 520mm x 110mm space on the front and rear splitters are to be reserved for a championship sponsors decals.

6.38.5 MGOC/BARC decals are to be positioned on each side of the car, the location is free.

6.38.6 MGOC reserves the right to request that additional decals are fitted at any time.

6.38.7 All decals are provided on request by the MGOC to registered competitors. Any car not displaying the required decals may be subject to appropriate penalties as defined in 4.3.6.

## 7. TECHNICAL REGULATIONS – CLASS F

**THE ELIGIBILITY SCRUTINEER RESERVES THE RIGHT TO SEAL AND SUBSEQUENTLY DISMANTLE ANY PART OF A COMPETING CAR. ANY REBUILDING COSTS WILL BE BORNE BY THE COMPETITOR.**

### 7.1 INTRODUCTION:

- 7.1.1 The term **OEM** (Original Equipment Manufacture) as used hereafter relates to “Standard Parts” and “Standard Pattern Parts” as defined in Clause 3.7.
- 7.1.2 No modifications are permitted from the **OEM** specification other than those specified hereafter or listed in official Technical Bulletins as issued by BARC. It must be clearly understood that if the following texts do not clearly state that you can do the works you should work on the principle that you cannot.
- 7.1.3 Where items are listed in the following texts under the headings “Prohibited Modifications”, it must be understood that this is not an exhaustive list and the references made in 7.1.2 must be understood and acknowledged.
- 7.1.4 For technical reference the following MG Rover documents apply:
- MGF Workshop Manual – RCL0051
  - MG TF Workshop Manual RCL0493
  - PGI Gearbox Manual – RCL 0124
  - K Series Engine Overhaul Manual – RCL 0057

### 7.2 GENERAL DESCRIPTION:

- 7.2.1 Class F is open to 1.8 VVC MGF and MG TF160 cars.
- 7.2.2 MOT certificates, Insurance and Road Fund licences are not required.
- 7.2.3 With the exception of those items specifically permitted within these Regulations, no MG Rover or MG dealer offered factory options are permitted without the written approval of the Championship Co-ordinator.

### 7.3 SAFETY REQUIREMENTS:

- 7.3.1 NCR 7.3 Safety Requirements will apply.
- 7.3.2 Six point roll cages are mandatory for all cars.
- 7.3.3 No part of the roll cage is permitted to project through the front bulkhead or into the engine compartment.
- 7.3.4 Towing eyes in accordance with NCR 12.13.1.3 – 1.4 must be fitted.

### 7.4 BODYSHELL:

- 7.4.1 It is permitted to upgrade a factory supplied 1.8i car to VVC specification providing that the conversion is total in all respects, including interior trim and dashboard.
- 7.4.2 MGTF bodyshells and body panels may be used to reshell an MGF but such cars must use the MGF subframes and Hydragas suspension and must comply completely with all MGF mechanical and electrical specifications.
- 7.4.3 MGTF160 cars must comply completely with all MGTF160 mechanical and electrical specifications and must use all body and structural components as **OEM** fitment to TF160 cars. The fitting of any MGF specific components to an MGTF is prohibited.
- 7.4.4 The factory fitted bodyshell cross braces may be removed from TF bodyshells.
- 7.4.5 Non-**OEM** accessories or cosmetic modifications which will not influence the cars overall performance will be allowed subject to the written approval of the Championship Co-ordinator.
- 7.4.6 Fibreglass bonnets and boot lids to the **OEM** MG Rover shape are permitted.
- 7.4.7 The fitting of MG Rover accessory rear spoiler is permitted.
- 7.4.8 Cars must run with an either an **OEM** factory hardtop or a similar style aftermarket style hardtop. The glass rear window on an **OEM** hardtop may be replaced with polycarbonate.
- 7.4.9 The bodyshell may be seam welded.
- 7.4.10 MGTF front and rear bumper panels, boot lid and headlamps may be fitted to MGF.



7.4.11 The original MG Rover exterior rear view mirrors must be fitted to each side of the car.

## 7.5 INTERIOR:

7.5.1 The driver seat may be changed and the standard seat fixings/runners removed or modified. The passenger seat may be removed.

7.5.2 Interior carpets may be removed.

7.5.3 The rear parcel shelf, the trim panels behind the seats and the rear bulkhead finisher can be removed or modified to accommodate the roll cage.

7.5.4 The entire hood assembly can be removed.

7.5.5 All **OEM** interior trim, dashboard and standard fittings must remain in place and the dashboard carcass is to remain unmodified. Additional switches, gauges and pull cables may be fitted.

7.5.6 Door trim panels must be fitted but may be trimmed to accommodate the roll cage door bars. The use of non-standard door trim panels is permitted.

7.5.7 The steering column lock and central locking mechanisms must be disabled.

7.5.8 Airbags must be disabled.

7.5.9 Both front window winder motors must remain fitted and operational.

7.5.10 Sound deadening may be removed.

7.5.11 On MGF and TF the heater and ducting may be removed if desired.

## 7.6 ENGINE:

### Permitted Modifications

7.6.1 Engine mounting material is free.

7.6.2 Two 1.5mm holes are to be drilled in adjacent cam cover bolts for the purpose of fitting engine seals.

7.6.3 The maximum bore and stroke dimensions are to be 80.00mm and 89.30mm respectively.

7.6.4 The use of Chinese manufactured replacement K series cylinder blocks is permitted. These may be machined only where necessary to allow the fitment of the **OEM** K series crankshaft position sensor.

7.6.5 The crankshaft must be **OEM** parts as fitted by MG Rover to the production VVC160 K series engine.

7.6.6 Connecting rods must be the **OEM** type or maXpeeding CR-RK-133.  
OEM conrods may be bushed or reamed to accept a fully floating gudgeon pin.

7.6.7 Crankshaft journals may be reground to 0.25mm undersize and the appropriate bearing shells fitted. No other modifications are permitted and the stroke of the crankshaft must remain as standard.

7.6.8 Aftermarket pistons and liners are permitted but must be to the exact specification, profile and material of the **OEM** MG Rover components as fitted to VVC or 1.8 K series engines.

Pistons may be machined only to accept the circlips of a fully floating gudgeon pin.

7.6.9 The overall height of the cylinder block including the ladder rail must be not less than 281.50mm.

7.6.10 The distance from the top of the liner to the shoulder of the liner must be not less than 50mm.

7.6.11 The flywheel is to be steel, the minimum weight with ring gear is 2.8kg.

7.6.12 Cylinder heads may be skimmed but the depth reference datum in the head casting must remain visible.

7.6.13 Exhaust valves must conform to **OEM** specification in their entirety, with a maximum head diameter of 27.5mm, a minimum stem diameter of 6mm and a single 45 degree face. It is permitted to have a carbon break in the valve stem to a minimum diameter of 5.5mm.

7.6.14 Inlet valves must conform to **OEM** specification in their entirety, with a maximum head diameter of 31.5mm and a minimum stem diameter of 6mm along its entire length. They must have a 45 degree face with a maximum of one single 30 degree back cut.

7.6.15 Valve seats may be cut to a maximum of three angles and must conform in their entirety to the dimensions and specifications laid out within the MG Rover K Series Overhaul Manual (RCL 0057) . The valve seats must not be blended into the combustion chambers or port walls.



- 7.6.16 Valve springs and hydraulic lifters must be to **OEM** specification
- 7.6.17 Aftermarket valve spring top caps are permitted.
- 7.6.18 Inlet and exhaust cam profiles must remain exactly as the **OEM** MG Rover items.
- 7.6.19 Cam timing must remain as **OEM**.
- 7.6.20 The **OEM** Steel Elastomer or later multi-shim head gaskets are permitted. The early or later type oil rail may be used.
- 7.6.21 The **OEM** fuel tank breather system including the charcoal canister/purge valve must be fitted.

#### Prohibited Modifications

- 7.6.22 Forged pistons.
- 7.6.23 Aftermarket or non-**OEM** MG Rover camshafts.
- 7.6.24 Any machining to the cylinder head combustion chambers or inlet/exhaust ports.
- 7.6.25 Any machining to the valves or valve seats other than as detailed in 7.6.12 and 7.6.13.
- 7.6.26 The engine block, oil rail, crankshaft, conrods, pistons and liners must be to **OEM** specification and dimensions. They may not be machined, have any material added or removed, or be modified in any way except as detailed in 7.6.4, 7.6.6 and 7.6.8.
- 7.6.27 Any machining to the crankshaft or camshaft sprocket.
- 7.6.28 Any means of modifying the cam timing eg. vernier timing pulleys, offset or modified camshaft location dowels.

### **7.7 COOLING SYSTEM:**

- 7.7.1 The **OEM** radiator must be fitted.
- 7.7.2 It is permitted to fit an aftermarket air/liquid oil cooler.
- 7.7.3 The main radiator cooling fan must be retained but the supplementary engine bay cooling fan may be removed.
- 7.7.4 It is permitted to fit a Pressure Relief Remote Thermostat (PRRT) and associated hoses.

### **7.8 INDUCTION SYSTEM:**

- 7.8.1 The fitting of an alternative proprietary made air filter and induction kit is allowed. This may be ducted to the left side rear quarter panel air intake vent.
- 7.8.2 **OEM** MG Rover 48mm or 52mm throttle bodies are permitted.
- 7.8.3 The Air Inlet Control Valve must remain in place but may be disabled.

### **7.9 EXHAUST SYSTEM:**

- 7.9.1 The **OEM** exhaust downpipe and manifold must be fitted. The later six bolt type as fitted to 160 cars may be fitted to earlier cars.
- 7.9.2 An operational catalytic converter must be fitted, this is to be a minimum 100 cell design and must be fitted in the original factory fitted location.
- 7.9.3 The exhaust system beyond the catalytic convertor is free but the system must exit at the rear of the car.
- 7.9.4 The welding nodules on the inner face of the exhaust manifold may be removed but the internal bore must not exceed 36mm at any point.
- 7.9.5 The welding nodules on the inner face of the manifold downpipe may be removed but the internal bore must not exceed 41.5mm at any point.

### **7.10 IGNITION SYSTEM:**

- 7.10.1 Cars fitted with MEMS 2 may be converted to run the later MEMS 3 ECU.
- 7.10.2 The original MG Rover MEMS2 or MEMS3 ECU must be retained but the mapping within it must be modified by Superchips to MGOC Championship specification MGOC/MEMS2 or by Kmaps.co.uk to MGOC Championship specification MGOC/MEMS3. ECUs modified by any other suppliers or to any other standard are not permitted.



### 7.10.3 MEMS2 Cars

At selected race meetings, the ECU's on MEMS2 cars may be sealed and removed by the appointed Motorsport UK Scrutineer. The sealed ECU's will be sent to Superchips Ltd, who, in the presence of an Motorsport UK Eligibility Scrutineer, will examine the map within the ECU to ascertain if it conforms with the approved MEMS2/MGOC specification.

### 7.10.4 MEMS3 Cars

7.10.4.1 The ECU on any selected MEMS 3 equipped car may be sealed and either examined at the circuit or removed from the car and sent to Kmaps.co.uk who will ascertain if the map within the ECU complies with specification MGOC/MEMS3FZ.

7.10.4.2 MG Owners' Club will hold an ECU modified by Kmaps.co.uk to Championship specification MGOC/MEMS3FZ. At selected race meetings, the appointed Motorsport UK scrutineer may request that the ECU fitted to a car is replaced with the MG Owners' Club ECU. The Motorsport UK Eligibility scrutineer is at liberty to decide which car is subjected to this procedure or to hold a ballot of all cars competing in Class F. In the event that any driver refuses to fit the MGOC ECU, the Motorsport UK Eligibility scrutineer will deem the car ineligible to take part in Class F and the car will be placed in the Invitation class until such time as the MGOC ECU is fitted to their satisfaction.

## 7.11 **SUSPENSION:**

### Permitted Modifications

7.11.1 MGF dampers may be changed for a direct replacement type with a single method of bump/rebound adjustment with an integral reservoir.

7.11.2 MGF must retain the **OEM** Hydragas suspension. The displacer type is free, this may be individually inflated with a separate valve operating each unit. The under floor Hydragas connection pipes may be removed.

7.11.3 On MGF it is permitted to strengthen the front and rear damper mountings.

7.11.4 On MGF the production front and rear bump stops must be retained in their original position.

7.11.5 On MGF suspension lowering knuckles are permitted.

7.11.6 MGTF dampers may be changed to adjustable platform type a single method of bump/rebound adjustment with an integral reservoir. Spring rates are free.

7.11.7 The rear dampers may be droop restricted by modifying the internal bump stops or by fitting a mechanical tether.

7.11.8 Suspension and subframe bush material is free.

7.11.9 Ride height is free subject to NCR 7.2.22.12

### Prohibited Modifications

7.11.10 Spherical bearings (eg. rose joints).

7.11.11 Dampers with more than a single method of bump/rebound adjustment and/or remote reservoirs.

## 7.12 **TRANSMISSION:**

### Permitted Modifications

7.12.1 Clutch plate material is free but the clutch must be of single plate design and must mount to the bolt and dowel holes of an original **OEM** flywheel.

7.12.2 The only gearbox permitted is MG Rover type C4. The gearbox ratios are to be:

- 1st : 3.167 / 2nd : 1.842 / 3rd : 1.308 / 4th : 1.033 / 5th : 0.765

7.12.3 The final drive ratio is to be 4.2:1.

7.12.4 The use of an aftermarket modified rear upright with larger wheel bearing is permitted on safety and reliability grounds provided the rear track width (measured across the rear wheels) remains as **OEM**.

7.12.5 It is permitted to reduce the length of the gear lever and remove the balance weight.

7.12.6 The gear linkage attachment to the gearbox is free and may be wire locked to prevent dislocation of the ball joint.

7.12.7 Non-**OEM** bushes may be fitted to the gearbox stabiliser bar.

### Prohibited Modifications

- 7.12.8 Any form of locked, limited slip or torque sensing differentials.
- 7.12.9 Any form of traction control or launch control device.

### **7.13 ELECTRICAL SYSTEMS:**

- 7.13.1 It is permitted to fit a link across the fuel cut-out inertia switch.
- 7.13.2 Data logging systems are permitted.
- 7.13.3 The standard MGF/TF headlamps must be retained and be fully operational. Plastic film or covers may be fitted
- 7.13.4 Gel type batteries are permitted but must be fitted in the original location.
- 7.13.5 All sensors and factory fitted wiring must remain intact. No alterations are permitted unless approved in writing by the appointed Championship Eligibility Scrutineer.
- 7.13.6 The alternator charging system must remain fully operational at all times.

### **7.14 BRAKES:**

- 7.14.1 The **OEM** front fog lights may be removed and replaced with ducting but the original aperture dimensions must not be increased.
- 7.14.2 Uprated brake pads, linings and brake hoses may be fitted.
- 7.14.3 The brake servo unit may be braced to the bulkhead with a strengthening bracket.
- 7.14.4 On MGF, the front brakes may be modified to accept the 283mm diameter discs fitted as **OEM** to MG ZR160 and re-drilled for an MGF stud pattern. A modified brake caliper carrier and alloy brake caliper spacer may be fitted. The rear discs on MGF may be grooved, slotted or dimpled.
- 7.14.5 On TF160, all brake components must be as per the original **OEM** size and design.
- 7.14.6 The ABS system may be disabled or removed.
- 7.14.7 A pressure limiting valve may be fitted to the hydraulic line to the rear brakes, this must comply with NCR 12.13.5.4-5.5.

### **7.15 FUEL TANK/FUEL SYSTEM:**

- 7.15.1 Permitted Fuels as defined in NCR 8.1.1.7 must be used.
- 7.15.2 The **OEM** MG Rover fuel tank must be fitted. It may be baffled or foam filled.
- 7.15.3 The **OEM** MG Rover fuel pressure system and injectors must be retained with no changes or modifications.
- 7.15.4 The fuel pressure is to be minimum 2.8 bar, maximum 3.2 bar.

### **7.16 WHEELS/STEERING:**

- 7.16.1 Wheel camber and tracking angles are free.
- 7.16.2 MGF must use the **OEM** 15" x 6" wheels. These must not be modified to achieve the enhanced brake option as 7.14.4.
- 7.16.3 MGTF must use the **OEM** 16" x 7" wheels.
- 7.16.4 The entire EPAS (Electric Power Assisted Steering) system and the may be removed.
- 7.16.5 The steering column may be changed to an **OEM** non-EPAS type.

### **7.17 TYRES:**

- 7.17.1 Cars are required to use the following tyres:
  - MGF: 195/55R15 Toyo 888R (GG Medium compound only)
  - MGTF160: 195/50R16 Toyo 888R (GG Medium compound only)
- 7.17.2 The compound marking on the sidewall is to remain clearly visible at all times. Any tyre not clearly displaying the manufacturer's original compound marking will be deemed non-compliant.
- 7.17.3 The nominated tyre supplier is: Adams and Page, Lincoln Road, Cressex Estate, High Wycombe, Bucks, HP12 3RO. Tel: 01494 445389



ADRIAN FLUX  
Insurance for the Independent



## **7.18 WEIGHTS:**

7.18.1 The minimum weight as the car finishes qualifying or race with the driver on board are as follows:

- MGF: 1100kg
- MGTF160: 1100kg

7.18.2 Ballast is permitted, this must be securely fixed in the front passenger footwell.

7.18.3 The Championship Organisers reserve the right to review and alter weight limits up to a maximum of two occasions per year with a minimum of 14 days notice to the Motorsport UK and competitors concerned.

## **7.19 NUMBERS AND CHAMPIONSHIP DECALS:**

7.19.1 Race numbers are to be fitted to 430mm wide x 300mm high white number backgrounds on each door and the bonnet or yellow numbers may be fitted on the rear doors/hardtop as stated in NCR 12.4.5

7.19.2 An Adrian Flux sun-strip is to be affixed to the top of the front windscreen.

7.19.3 Adrian Flux decals are to be fitted to each side of the car, the position is unrestricted.

7.19.4 The 520mm x 110mm space on the front and rear splitters are to be reserved for a championship sponsors decals.

7.19.5 MGOC/BARC decals are to be positioned on each side of the car but the position is free.

7.19.6 MGOC reserves the right to request that additional decals are fitted at any time.

7.19.7 All decals are provided on request by the MGOC to registered competitors. Any car not displaying the required decals may be subject to appropriate penalties as defined in 4.3.6.

## 8. TECHNICAL REGULATIONS – CLASS Z

**THE ELIGIBILITY SCRUTINEER RESERVES THE RIGHT TO SEAL AND SUBSEQUENTLY DISMANTLE ANY PART OF A COMPETING CAR. ANY REBUILDING COSTS WILL BE BORNE BY THE COMPETITOR.**

### 8.1 INTRODUCTION:

- 8.1.1 The following Technical Regulations are set out in accordance with the Motorsport UK specified format.
- 8.1.2 The term **OEM** (Original Equipment Manufacturer) as used hereafter relates to “Standard Parts” and “Standard Pattern Parts” as defined in Clause 3.7.
- 8.1.3 No modifications are permitted from the **OEM** specification other than those specified hereafter or listed in official Technical Bulletins as issued by BARC. It must be clearly understood that if the following texts do not clearly state that you can do the works you should work on the principle that you cannot.
- 8.1.4 Where items are listed in the following texts under the headings “Prohibited Modifications”, it must be understood that this is not an exhaustive list and the references made in 8.1.3 must be understood and acknowledged.
- 8.1.5 For technical reference the following MG Rover documents apply:
- System Description Manual – RCL0379
  - Service Procedure Manual – RCL 0534
  - PGI Gearbox Manual – RCL 0124
  - K Series Engine Overhaul Manual – RCL 0057

### 8.2 GENERAL DESCRIPTION:

- 8.2.1 Class Z is open to MG ZR170 and MG ZS170 cars
- The MG ZS170 is a hybrid car comprised of the bodyshell, suspension and braking system of the MG ZS120 as described within the Regulations for Class B but fitted with the engine, gearbox and ancillaries from the MG ZS170 as described in the Regulations for Class Z.
- 8.2.2 MOT certificates, Insurance and Road Fund licences are not required.
- 8.2.3 With the exception of those items specifically permitted within these Regulations, no MG Rover or MG dealer offered factory options are permitted without the written approval of the Championship Co-ordinator.

### 8.3 SAFETY REQUIREMENTS:

- 8.3.1 NCR 7.3 Safety Requirements will apply.
- 8.3.2 Six point roll cages are mandatory for all cars.
- 8.3.3 No part of the roll cage is permitted to project through the front bulkhead or into the engine compartment.
- 8.3.4 Towing eyes in accordance with NCR 12.13.1.3 – 1.4 must be fitted.

### 8.4 BODYSHELL:

- 8.4.1 Left hand drive cars are not permitted.
- 8.4.2 Bodyshells from ZR105 and ZR120 may be used but must conform totally to ZR170 specification ZS170 bodyshells conforming to Class B regulations may also be used in Class Z.
- 8.4.3 Non-**OEM** or aftermarket accessories or cosmetic modifications which will not influence the cars overall performance will be allowed subject to the written approval of the Organisers.
- 8.4.4 ZS170 only may use fibreglass bonnet and boot tailgate, these must be the original MG Rover profile. Alternatively, the **OEM** steel bonnet and/or tailgate may be lightened.
- 8.4.5 On ZS170 only, the rear window may be replaced by 4mm polycarbonate.
- 8.4.6 The bodyshell may be seam welded.
- 8.4.7 The original MG Rover exterior rear view mirrors must be fitted to each side of the car.
- 8.4.8 On board air jacks are permitted.



## 8.5 INTERIOR:

- 8.5.1 All interior trim, dashboard and standard fittings must remain in place and the dashboard carcass is to remain unmodified. Additional switches, gauges and pull cables may be fitted.
- 8.5.2 The driver seat may be changed and the standard seat fixings/runners removed or modified.
- 8.5.3 The passenger seat, rear seat and carpets may be removed.
- 8.5.4 The use of non-standard door trim panels is permitted.
- 8.5.5 The steering wheel may be changed.
- 8.5.6 The rear quarter trim panels and roof lining may be removed.
- 8.5.7 The steering column lock and central locking mechanisms must be disabled.
- 8.5.8 Airbags may be removed or disabled.
- 8.5.9 Air-conditioning systems may be removed.
- 8.5.10 On ZS170 only, the door window winders may be removed and the glass side and rear door windows and rear screen may be replaced with polycarbonate to NCR 7.2.22.8. The driver's door window must incorporate a sliding access panel.
- 8.5.11 On ZR170 only, the door window glass and both front window winder motors must remain fitted and operational.
- 8.5.12 Sound deadening may be removed.
- 8.5.13 The **OEM** heater must be fitted and be fully operational using the **OEM** ducting and vents.
- 8.5.14 On ZS170 only the heater, motor, controls and ducting may be removed. The dashboard must remain unmodified

## 8.6 ENGINE:

### Permitted Modifications

- 8.6.1 Engine mounting material is free.
- 8.6.2 Two 1.5mm holes are to be drilled in adjacent cam cover bolts for the purpose of fitting engine seals.
- 8.6.3 The maximum bore and stroke dimensions are to be 80.00mm and 89.30mm respectively.
- 8.6.4 The use of Chinese manufactured replacement K series cylinder blocks is permitted. These may be machined only where necessary to allow the fitment of the **OEM** K series crankshaft position sensor.
- 8.6.5 The crankshaft must be the **OEM** part as fitted by MG Rover to the production VVC160 K series engine.
- 8.6.6 Connecting rods must be the OEM type or maXpeeding CR-RK-133.  
OEM conrods may be bushed or reamed to accept a fully floating gudgeon pin.
- 8.6.7 Crankshaft journals may be reground to 0.25mm undersize and the appropriate bearing shells fitted. No other modifications are permitted and the stroke of the crankshaft must remain as standard.
- 8.6.8 Aftermarket pistons and liners are permitted but must be to the exact specification, profile and material of the **OEM** MG Rover components as fitted to VVC or 1.8 K series engines.  
Pistons may be machined only to accept the circlips of a fully floating gudgeon pin.
- 8.6.9 The overall height of the cylinder block including the ladder rail must be not less than 281.50mm.
- 8.6.10 The distance from the top of the liner to the shoulder of the liner must be not less than 50mm.
- 8.6.11 The flywheel is to be steel, the minimum weight with ring gear is 2.8kg.
- 8.6.12 Cylinder heads may be skimmed but the depth reference datum in the head casting must remain visible.
- 8.6.13 Exhaust valves must conform to **OEM** specification in their entirety, with a maximum head diameter of 27.5mm, a minimum stem diameter of 6mm and a single 45 degree face. It is permitted to have a carbon break in the valve stem to a minimum diameter of 5.5mm.
- 8.6.14 Inlet valves must conform to **OEM** specification in their entirety, with a maximum head diameter of 31.5mm and a minimum stem diameter of 6mm along its entire length. They must have a 45 degree face with a maximum of one single 30 degree back cut.

- 8.6.15 Valve seats may be cut to a maximum of three angles and must conform in their entirety to the dimensions and specifications laid out within the MG Rover K Series Overhaul Manual (RCL 0057) . The valve seats must not be blended into the combustion chambers or port walls.
- 8.6.16 Valve springs and hydraulic lifters must be to **OEM** specification
- 8.6.17 Aftermarket valve spring top caps are permitted.
- 8.6.18 Inlet and exhaust cam profiles must remain exactly as the **OEM** MG Rover items.
- 8.6.19 Cam timing must remain as **OEM**.
- 8.6.20 The **OEM** Steel Elastomer or later multi-shim head gaskets are permitted.
- 8.6.21 The early or later type oil rail may be used.
- 8.6.22 The **OEM** fuel tank breather system including the charcoal canister/purge valve must be fitted.

#### Prohibited Modifications

- 8.6.23 Forged pistons.
- 8.6.24 Non-**OEM** camshafts.
- 8.6.25 Any machining to the cylinder head combustion chambers or inlet/exhaust ports.
- 8.6.26 Any machining to the valves or valve seats other than as detailed in 8.6.12 and 8.6.13.
- 8.6.27 The engine block, oil rail, crankshaft, conrods, pistons and liners must be to **OEM** specifications and dimensions. They may not be machined, have any material added or removed or be modified in any way except as detailed in 8.6.4, 8.6.6 and 8.6.8.
- 8.6.28 Any machining to the crankshaft or crankshaft sprocket.
- 8.6.29 Any means of modifying the cam timing eg. vernier timing pulleys, offset or modified cam dowels.

### **8.7 COOLING SYSTEM:**

- 8.7.1 The **OEM** radiator or an identical aftermarket version must be fitted.
- 8.7.2 Additional or uprated oil coolers may be fitted.
- 8.7.3 It is permitted to fit a Pressure Relief Remote Thermostat (PRRT) and associated hoses.

### **8.8 INDUCTION SYSTEM:**

- 8.8.1 The fitting of an alternative proprietary made air filter and induction kit is allowed.
- 8.8.2 Ducting may be fitted to the induction kit, the front panel may be cut to accommodate this.
- 8.8.3 The **OEM** MG Rover 52mm throttle body must be used.
- 8.8.4 The Air Inlet Control Valve must remain in place but may be disabled.

### **8.9 EXHAUST SYSTEM:**

- 8.9.1 The **OEM** exhaust downpipe and manifold must be fitted. The later six bolt type as fitted to 160 cars may be fitted to earlier cars.
- 8.9.2 An operational catalytic converter must be fitted, this is to be a minimum 100 cell design and must be fitted in the straight section of the exhaust running along the centre line of the car.
- 8.9.3 The exhaust system beyond the catalytic convertor is free but the system must exit at the rear of the car.
- 8.9.4 The welding nodules on the inner face of the exhaust manifold may be removed but the internal bore must not exceed 36mm at any point.
- 8.9.5 The welding nodules on the inner face of the manifold downpipe may be removed but the internal bore must not exceed 41.5mm at any point.

### **8.10 IGNITION SYSTEM:**



- 8.10.1 The original MG Rover MEMS3 ECU must be retained but the mapping within it must be modified by Kmaps.co.uk to MGOC Championship specification MGOC/MEMS3FZ. ECU's modified by any other suppliers or to any other standard are not permitted.
- 8.10.2 The ECU on any selected MEMS 3 equipped car may be sealed and either examined at the circuit or removed from the car and sent to Kmaps.co.uk who will ascertain if the map within the ECU complies with specification MGOC/MEMS3FZ.
- 8.10.3 MG Owners' Club will hold an ECU modified by Kmaps.co.uk to Championship specification MGOC/MEMS3FZ. At selected race meetings, the appointed Motorsport UK Eligibility scrutineer may request that the ECU fitted to a car is replaced with the MG Owners' Club ECU. The scrutineer is at liberty to decide which car is subjected to this procedure or to hold a ballot of cars competing in Class Z. In the event that any driver refuses to fit the MGOC ECU, the scrutineer will deem the car ineligible to take part in Class Z and the car will be placed in the Invitation class until such time as the MGOC ECU is fitted to their satisfaction.

## 8.11 SUSPENSION:

### Permitted Modifications

- 8.11.1 Dampers may be changed to an adjustable platform type but must have a single method of bump/rebound adjustment.
- 8.11.2 Spherical bearings may be fitted in the lower rear damper mounts
- 8.11.3 Strut braces may be fitted across the front and rear suspension mounts.
- 8.11.4 Adjustable top suspension mounts may be fitted. The suspension turrets may be modified to accommodate these.
- 8.11.5 Suspension and rear H frame bushes and engine mount material is free.
- 8.11.6 Spring rates are free.
- 8.11.7 Ride height is free subject to NCR 7.2.22.12.
- 8.11.8 The rear dampers may be droop restricted only by modifying the internal bump stops or by fitting a mechanical tether.

### Prohibited Modifications

- 8.11.9 Spherical bearings (eg. rose joints) except in dampers (refer 8.11.2) and suspension top mounts (refer 8.11.4)
- 8.11.10 Dampers with more than a single adjustment for bump and a single adjustment for rebound.
- 8.11.11 Dampers with remote reservoirs.
- 8.11.12 Rear anti-roll bars

## 8.12 TRANSMISSION:

### Permitted Modifications

- 8.12.1 The clutch plate material is free but the clutch must be of single plate design and must mount to the bolt and dowel holes of an original **OEM** flywheel.
- 8.12.2 The only gearbox permitted is MG Rover type G4. The gearbox ratios are to be:
- 1st: 3.250 / 2nd: 1.894 / 3rd: 1.307 / 4th: 1.033 / 5th: 0.848
- 8.12.3 The final drive ratio is to be 4.2:1.
- 8.12.4 The gear linkage attachment to the gearbox is free and may be wire locked to prevent dislocation of the ball joint.
- 8.12.5 Non-**OEM** bushes may be fitted to the gearbox stabiliser bar.

### Prohibited Modifications

- 8.12.6 Any form of locked, limited slip or torque sensing differentials.
- 8.12.7 Any form of traction control or launch control device.



### **8.13 ELECTRICAL SYSTEMS:**

- 8.13.1 It is permitted to fit a link across the fuel pressure inertia switch.
- 8.13.2 Data logging systems are permitted.
- 8.13.3 The **OEM** headlamps must be retained and be fully operational. Plastic film or covers may be fitted to headlamps.
- 8.13.4 Gel type batteries are permitted but must be fitted in the original location.
- 8.13.5 All sensors and factory fitted wiring must remain intact. No alterations are permitted unless approved in writing by the appointed Eligibility Scrutineer.
- 8.13.6 The alternator charging system must remain fully operational at all times.
- 8.13.7 On ZS170 only, all window winder motors except the driver's side may be removed. The window winder motor on the driver's door must be retained and be fully operational.
- 8.13.8 The rear window wiper and motor may be removed.

### **8.14 BRAKES:**

- 8.14.1 Aftermarket brake discs of an identical design to the **OEM** discs may be fitted.
- 8.14.2 The **OEM** front fog lights may be removed and replaced with ducting but the original aperture dimensions must not be increased.
- 8.14.3 Uprated brake pads, linings and brake hoses may be fitted.
- 8.14.4 ZR170 brake discs are to be 283mm at the front and 260mm at the rear.
- 8.14.5 ZS170 brakes may be upgraded to ZR170 specification as per 8.14.4
- 8.14.6 The ABS system may be disabled or removed.
- 8.14.7 A pressure limiting valve may be fitted to the hydraulic line to the rear brakes, this must comply with NCR 12.13.5
- 8.14.8 The use of brake master cylinder BGZ06 is permitted

### **8.15 FUEL TANK/FUEL SYSTEM:**

- 8.15.1 Permitted Fuels as defined in NCR 8.1.1.7 must be used.
- 8.15.2 The **OEM** MG Rover fuel tank must be fitted. It may be baffled or foam filled.
- 8.15.3 The **OEM** MG Rover fuel pressure system and injectors must be retained with no changes or modifications.
- 8.15.4 The fuel pressure is to be minimum 2.8 bar, maximum 3.2 bar.

### **8.16 WHEELS/STEERING:**

- 8.16.1 Wheel camber and tracking angles are free.
- 8.16.2 Only the 16" inch wheels supplied by MG Rover and fitted as **OEM** to MG ZR160 saloons are permitted
- 8.16.3 Shouldered spacers may be fitted to the front hubs, these are to a maximum of 10mm thick.

### **8.17 TYRES:**

- 8.17.1 Cars are required to use the following tyres:
  - 195/50R16 Toyo 888R (GG medium compound only)
- 8.17.2 The compound marking on the sidewall is to remain clearly visible at all times. Any tyre not clearly displaying the manufacturer's original compound marking will be deemed non-compliant.
- 8.17.3 The nominated tyre supplier is: Adams and Page, Lincoln Road, Cressex Estate, High Wycombe, Bucks, HP12 3RO. Tel: 01494 445389.

## **8.18 WEIGHTS:**

8.18.1 The minimum weight as the car finishes qualifying or race with the driver on board is as follows:

- MG ZR170 : 1050kg
- MG ZS170 : 1050kg

8.18.2 Ballast is permitted, this must be securely fixed in the front passenger footwell.

8.18.3 The Championship Organisers reserve the right to review and alter weight limits up to a maximum of two occasions per year with a minimum of 14 days' notice to the Motorsport UK and competitors concerned.

## **8.19 NUMBERS AND CHAMPIONSHIP DECALS:**

8.19.1 Race numbers are to be fitted to 430mm wide x 300mm high white number backgrounds on each door and the bonnet or yellow numbers may be fitted on the windscreen and rear door windows as defined in NCR 12.4.5

8.19.2 An Adrian Flux sun-strip is to be sun-strip is to be affixed to the top of the front windscreen.

8.19.3 Adrian Flux decals are to be positioned on each side of the car, the location is free.

8.19.4 The 520mm x 110mm space on the front and rear splitters are to be reserved for a championship sponsors decals.

8.19.5 MGOC/BARC decals are to be positioned on each side of the car but the position is free.

8.19.6 MGOC reserves the right to request that additional decals are fitted at any time.

8.19.7 All decals are provided on request by the MGOC to registered competitors. Any car not displaying the required decals may be subject to appropriate penalties as defined in 4.3.6.

## 9. TECHNICAL REGULATIONS – CLASS I: INVITATION CLASS

**THE ELIGIBILITY SCRUTINEER RESERVES THE RIGHT TO SEAL AND SUBSEQUENTLY DISMANTLE ANY PART OF A COMPETING CAR. ANY REBUILDING COSTS WILL BE BORNE BY THE COMPETITOR OF THAT CAR.**

### 9.1 INTRODUCTION:

- 9.1.1 Acceptance of an entry into Class I will be solely at the discretion of MGOC.
- 9.1.2 Any car entering Class I will be expected to conform to the spirit of the MGOC Championship in being essentially a road going race car. Entries will be encouraged on the basis that cars are expected to meet, but not exceed, the performance standards of other competing cars.
- 9.1.3 Any driver wishing to enter a car into Class I must submit full details of the car to MGOC for approval a minimum of ten days prior to the meeting.
- 9.1.4 Competitors entering this Class will not be eligible for Championship points.
- 9.1.5 Entries will be accepted for Class I on the basis that grid places are available on the official date of entries closing as advised by BARC.

### 9.2 TYRES:

- 9.2.1 Any treaded tyre from NCR 8.4 List 1A, 1B or 1C may be used but cars are encouraged to use Toyo 888R (GG Medium compound) tyres.

### 9.3 NUMBERS AND CHAMPIONSHIP DECALS:

- 9.3.1 Race numbers will be allocated by MGOC.
- 9.3.2 Race numbers are to be fitted to 430mm wide x 300mm high white number backgrounds on each door and the bonnet. Alternatively, yellow numbers may be fitted to the rear side windows and windscreen as stated in NCR 12.4.5
- 9.3.3 MGOC/BARC decals are to be positioned on each side of the car, but the position is free.
- 9.3.4 Adrian Flux sun-strips are recommended but are not mandatory.
- 9.3.5 Adrian Flux decals are to be positioned on each side of the car; the location is free.
- 9.3.6 MGOC reserve the right to request that decals from other championships are removed or obscured.
- 9.3.7 MGOC reserve the right to request that additional decals are fitted at any time.

## 10. APPENDICES

The following Commercial Regulations are “contractual” between the Entrant and / or Driver and the Organisers and / or Promoters and are not considered by Motorsport UK. Accordingly, the application of these Commercial Regulations by the Organisers and / or Promoters will not be subject to the Judicial processes of either the Championship Stewards and / or the Motorsport UK / MSC.

### 10.1 MGOC CONDUCT AND DRIVING STANDARDS:

10.1.1 In the event that a driver receives licence penalty points for a driving offence under the provisions of NCR 2.1.1.13, that driver will receive formal notification from MGOC as to their future conduct. In the event of further infringements during the same season the MGOC reserve the right to suspend that drivers Club Membership for the next Championship meeting hence that driver will not comply with Championship Regulation 1.3.2 and thus cannot race. Further or subsequent similar infringements may result in the permanent suspension of Club Membership.

The decision to suspend MGOC Club membership and the length of any such suspension will be determined by the General Manager of MGOC whose decision will be final and not subject to appeal.

10.1.2 Drivers are reminded that they are held responsible for the conduct of all members of their team. Refer to NCR 6.1.1.4.

### 10.2 RACE ORGANISING CLUB & CONTACTS:

BARC, Thruxton Circuit, Andover, Hampshire, SP11 8PN

Tel: 01264 882209

E-mail: [competitions@barc.net](mailto:competitions@barc.net)

Championship Co-Ordinator:

Name: David Wheadon

Tel: 01264 882209

Email: [david.wheadon@barc.net](mailto:david.wheadon@barc.net)

Eligibility Scrutineer:

Name: Richard Hargreaves

Tel: 07434 967 572

Email: [richard.hargreaves.2010@btinternet.com](mailto:richard.hargreaves.2010@btinternet.com)

MGOC Drivers Representative:

Name: Jim Baynam

Tel: 07871 119785

Email: [baynam@btinternet.com](mailto:baynam@btinternet.com)

MGOC Racing Administration:

Name: Linda Empson

Address: MG Owners' Club, Octagon House, Swavesey, Cambridge, CB24 4QZ

Tel: 01954 231125

Email: [raceteam@mgownersclub.co.uk](mailto:raceteam@mgownersclub.co.uk)

#### Championship Technical Advisors

Any of the persons detailed below can provide technical support and advisory assistance to any Motorsports UK appointed official and, if requested be present in parc-fermé or at any on or off circuit technical examinations.

1. Roger Parker - MG Owners Club
2. Jonathan Kimber - MG Owners Club
3. Mark Stacey - Kmaps
4. Malcolm Gammons - Brown and Gammons
5. Kevin Bull - KB Motorsport



A socially-minded standard of behaviour is expected from everyone within the motorsport community.

By participating in a Motorsport UK event in any capacity you agree to follow the values of the Respect Code:

Motorsportuk.org/racewithrespect  
#RaceWithRespect

### The Values

- **Respect**
- **Fair play**
- **Integrity**
- **Good Manners**
- **Self-Control**

I pledge to #RaceWithRespect and:

- Contribute to a welcoming and friendly environment that ensures the safety and welfare of all participants.
- Always behave with integrity and uphold fairness in the sport; play my part in keeping the sport safe through my actions
- Treat everyone with respect, regardless of their gender, ethnic or social background, language, religious or other beliefs, disability, sexual identity or other status
- Recognise that we all represent the sport and therefore have a duty to be polite and respectful to all staff, officials, fellow competitors, volunteers, as well as fans and supporters
- Respect the rules, regulations and authority of the officials and Motorsport UK

Any breach of these obligations may result in disciplinary action.



**11. REGISTRATION FORM**

**2026 MG OWNERS CLUB CHAMPIONSHIP**

**RACE ENTRIES WILL NOT BE ACCEPTED UNTIL A FULLY COMPLETED FORM IS SUBMITTED TO MG OWNERS CLUB**

NAME OF DRIVER:			
ADDRESS:			
POSTCODE:			
TEL (DAY):		MOBILE:	
EMAIL ADDRESS:			
AGE:		DATE OF BIRTH:	
NATIONALITY:			
COMPETITION LICENCE NO:		GRADE:	
BARC MEMBERSHIP NO:			
MGOC MEMBERSHIP NO:			
NAME OF ENTRANT (if applicable):			
TRANSPONDER NO: (if known)			

CAR:		MODEL:		CC:	
CLASS:	A:	B:	F:	Z:	I:

**DECLARATION TO BE COMPLETED BY ALL APPLICANTS**

I understand the MGOC Championship Technical Regulations and confirm that my car will comply with those Regulations.

I am a member of the MG Owners' Club confirm that the Championship registration fee of £40 has been paid to MGOC.

SIGNED:		DATE:	
---------	--	-------	--

**ONCE FULLY COMPLETED THIS FORM SHOULD BE RETURNED TO:**

**MGOC, Octagon House, Swavesey, Cambridge, CB24 4QZ or email to [lindae@mgownerclub.co.uk](mailto:lindae@mgownerclub.co.uk)**

FOR MGOC OFFICE USE ONLY			
REGISTRATION FEE	DATE RECEIVED:	DATE FORWARDED TO BARC	COMPETITION NO ALLOCATED:
£40			

Note: For forms submitted electronically, a typed name is acceptable.